

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 1 of 121

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name: Acetone  
REACH registration No.: 01-2119471330-49-XXXX  
Location Germany: 01-2119471330-49-0000  
Location Belgium: 01-2119471330-49-0005  
Location Mobile: 01-2119471330-49-0003

CAS-Number: 67-64-1  
EC-number: 200-662-2  
EU index number: 606-001-00-8

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

General use: Besides its application as a solvent Acetone is an important intermediate product of the chemical industry e.g. for manufacturing Methylmethacrylate, Methyl Isobutyl Ketone and Bisphenol A.

Identified uses:

##### Industrial use:

0	Generic exposure scenario (GES): Industrial Processes relevant for Acetone containing products (ES 1 - 11)	Page 14
1	Manufacture, processing and distribution of substances and mixtures *	Page 24
2	Use in laboratories	Page 27
3	Uses in coatings	Page 30
4	Use in binders and release agents	Page 33
5	Rubber production and processing	Page 36
6	Polymer manufacturing	Page 39
7	Polymer processing	Page 42
8	Use in cleaning agents	Page 45
9	Use in oil and gas field drilling and production operations	Page 48
10	Blowing agents	Page 51
11	Mining chemicals	Page 54

##### Professional use:

12	Generic exposure scenario (GES): Professional Processes relevant for Acetone containing products (ES 13 - 22)	Page 57
13	Use in laboratories	Page 72
14	Uses in coatings	Page 75
15	Use in binders and release agents	Page 78
16	Polymer production	Page 81
17	Polymer processing	Page 84
18	Use in cleaning agents	Page 87
19	Oil field well drilling and production operations	Page 90
20	Agrochemical uses	Page 93
21	De-icing and anti-icing applications	Page 96
22	Explosives manufacture & use	Page 99

##### Consumer use:

23	Generic exposure scenario (GES): Consumer uses of Acetone (ES 24 - 26)	Page 102
24	Uses in coatings	Page 117
25	Use in cleaning agents	Page 119
26	De-icing and anti-icing applications	Page 121

\* Examples for processing:

use as an intermediate,  
use as a monomer etc.,  
use as a solvent,  
use for the manufacturing of resins

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 2 of 121

### 1.3 Details of the supplier of the safety data sheet

Company name: INEOS Phenol GmbH  
Street/POB-No.: Dechenstraße 3  
Postal Code, city: 45966 Gladbeck  
Germany  
WWW: www.ineosphenol.com  
E-mail: msds.phenolde@ineos.com  
Telephone: +49 (0)2043 / 9 58-0  
Telefax: +49 (0)2043 / 9 58-900  
Dept. responsible for information:  
Telephone: +49 (0)2043 / 9 58-0 (Department ESHQ)  
E-mail: msds.phenolde@ineos.com  
Additional information: Location Belgium:  
INEOS Phenol Belgium NV  
Haven 1930 Geslecht 1, B-9130 Beveren  
Telephone: +32 3 730 13 50  
Telefax: +32 3 730 12 62  
On behalf of:  
INEOS Europe AG, INEOS Phenol Division,  
3, Avenue des Uttins, 1180 Rolle, Switzerland

### 1.4 Emergency telephone number

Telephone Germany: +49 (0)2043 / 9 58-233  
Telephone Belgium: +32 3 730 14 44  
or GIZ-Nord, Germany, Telephone: +49 (0)551-19240

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

#### Classification according to EC regulation 1272/2008 (CLP)

Flam. Liq. 2; H225 Highly flammable liquid and vapour.  
Eye Irrit. 2; H319 Causes serious eye irritation.  
STOT SE 3; H336 May cause drowsiness or dizziness.  
(EUH066) Repeated exposure may cause skin dryness or cracking.

### 2.2 Label elements

#### Labelling (CLP)



Signal word:

**Danger**

Hazard statements:

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 3 of 121

Precautionary statements: P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P243	Take action to prevent static discharges.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P403+P233 P405	Store in a well-ventilated place. Keep container tightly closed. Store locked up.
P501	Dispose of contents/container to hazardous or special waste collection point.

### 2.3 Other hazards

Vapours are moderately irritating to the mucous membranes.  
Higher doses may have a narcotic effect. Danger of metabolic acidosis.  
After ingestion: Gastric and intestinal problems.  
Other symptoms: Headache, dizziness, nausea, unconsciousness.

Results of PBT and vPvB assessment:

This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

## SECTION 3: Composition / information on ingredients

### 3.1 Substances

Chemical characterisation:  $C_3H_6O = H_3C-CO-CH_3$   
Acetone, Dimethyl ketone, 2-Propanone, Methyl ketone

CAS-Number: 67-64-1  
EC-number: 200-662-2  
EU index number: 606-001-00-8  
RTECS-Number: AL3150000  
Customs tariff number: 2914 11 00

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

General information: Move victim to fresh air, put at rest and loosen restrictive clothing. Do not allow victim to become chilled. Keep victim warm.  
If victim is at risk of losing consciousness, position and transport on their side. Call a physician immediately.

In case of inhalation: Move victim to fresh air, put at rest and loosen restrictive clothing.  
If breathing becomes irregular or ceases, apply rescue breathing or artificial respiration immediately, where required supply oxygen. Immediately get medical attention.

Following skin contact: Immediately remove any wetted clothing, shoes or stockings. After contact with skin, wash immediately with soap and plenty of water. Then cream your skin.  
In case of skin irritation, consult a physician.

After eye contact: Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently seek the immediate attention of an ophthalmologist.

After swallowing: If swallowed, do not induce vomiting; seek medical advice immediately and show this container or label.  
Give activated carbon, in order to reduce the resorption in the gastro-enteric tract.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 4 of 121

### 4.2 Most important symptoms and effects, both acute and delayed

Burning eyes and skin. fatigue, nausea, Headache, dizziness, unconsciousness.

In case of inhalation:

For the development of any overt signs of toxicity in humans, accidental exposures to extremely large amounts of acetone by inhalation of vapour or ingestion of liquid are necessary (e. g. several thousand ppm of acetone vapour).

In case of ingestion: Gastric and intestinal problems.

After contact with skin:

Irritant. Repeated exposure may cause skin dryness or cracking, due to defatting properties.

No indication for sensitising properties in humans.

After eye contact: Causes serious eye irritation.

### 4.3 Indication of any immediate medical attention and special treatment needed

Combat acidosis. Monitor alkali reserves. Monitor breathing.

If breathing becomes irregular or ceases, apply rescue breathing or artificial respiration immediately, where required supply oxygen.

Attention: several hours latency period. In severe cases, pneumonia or a pulmonary edema may develop.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media:

Extinguishing powder, alcohol resistant foam, carbon dioxide, water spray jet

Extinguishing media which must not be used for safety reasons:

Full water jet

### 5.2 Special hazards arising from the substance or mixture

Highly flammable liquid and vapour.

Explosive mixtures with air may even form at room temperature. Beware of reignition.

In case of fire may be liberated: Carbon monoxide and carbon dioxide.

### 5.3 Advice for firefighters

Special protective equipment for firefighters:

Wear a self-contained breathing apparatus and chemical protective clothing.

Additional information:

Hazchem-Code: •2YE

Heating will lead to pressure increase: Danger of bursting and explosion. Use fine water spray to cool endangered containers.

Move undamaged containers from immediate hazard area if it can be done safely.

Do not allow fire water to penetrate into surface or ground water.

Fire residuals and contaminated extinguishing water must be disposed of in accordance with the regulations of the local authorities.

Fire class: B

Mixtures with 4% acetone mixed with 96% water still have a flash point of 54 °C.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Eliminate all ignition sources if safe to do so. Remove persons not involved upwind.

Wear a self-contained breathing apparatus and chemical protective clothing.

Solvent-resistant protective clothing recommended.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 5 of 121

### 6.2 Environmental precautions

Plug leak if safely possible.  
Do not allow to enter drains, surface waters, basements or pits.  
When released into the environment, alert police and fire brigade.  
Seal all low level rooms. Danger of explosion!

### 6.3 Methods and material for containment and cleaning up

In case of spills of large quantities: Dam spills and pump to remove. Explosion protection required.

Absorb leftover product with non-flammable liquid-binding material (e.g. earth, sand, vermiculite or ground sand stone) and place in closed containers for disposal.

Flowing water: Dilution occurs quickly. In case of large spills/leaks inform appropriate local, state, and federal spill reporting authorities.

Standing water: Seal off. Remove all sources of ignition.

Additional information: Vapours spread at floor level. Cover drainage holes and evacuate basement. Dilute with plenty of water. Use only explosion-protected equipment/instruments.

Liquid: Very highly flammable. Liquid evaporates very quickly.

Vapours: Very highly flammable.

Vapours form potentially explosive mixtures with air. Heavier than air, they proceed at floor level and may backflash over great distances when ignited. Ignition by hot surfaces, sparks and open flames.

Solubility in water: complete

Mixtures with 4% acetone mixed with 96% water still have a flash point of 54 °C. In case of important spills, risk of ignition of the acetone-water mixture. Potentially explosive mixtures with air may form above water surface.

### 6.4 Reference to other sections

Refer additionally to section 8 and 13.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advices on safe handling: Provide adequate ventilation, and local exhaust as needed.  
Provide room air exhaust at ground level. Concentrated vapours are heavier than air.  
Avoid the formation of aerosol. Do not breathe vapours. Avoid contact with skin and eyes. Wear appropriate protective equipment.  
Use only explosion-protected equipment/instruments. Do not use air pressure.

Precautions against fire and explosion:  
Exposure to temperatures exceeding 50 °C will increase pressure: resulting in danger of bursting or explosion.  
Keep away from sources of ignition - No smoking.  
Take precautionary measures against static discharges. Beware of reignition.  
Potentially explosive mixture may form within partially empty containers.  
Emergency cooling must be provided for in case of a fire in the vicinity.  
Do not weld.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storerooms and containers:  
Keep container dry. Keep container tightly closed in a cool, well-ventilated place. Protect from direct sunlight.  
Steel, stainless steel, and aluminium are stable container materials. Copper may be attacked.  
Unsuitable container/equipment material: May attack plastics.  
Make sure spills can be contained, e.g. in sump pallets or kerbed areas.  
Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 6 of 121

Hints on joint storage: Do not store together with combustible or self-igniting materials or any highly flammable solids.  
Peroxide may form when product is exposed to light and air.

Further details: Potentially explosive mixture may form within partially empty containers.  
For outdoor storage: Use only equipment approved for use in 1 zone.  
For indoor storage: Use only equipment approved for use in 2 zone.

### 7.3 Specific end use(s)

solvent

## SECTION 8: Exposure controls/personal protection

All exposure relevant information (human health and environment) is summarised in annexes to this safety data sheet.

### 8.1 Control parameters

Occupational exposure limit values:

Type	Limit value
Europe: IOELV: TWA	1210 mg/m <sup>3</sup> ; 500 ppm
Great Britain: WEL-STEL	3620 mg/m <sup>3</sup> ; 1500 ppm
Great Britain: WEL-TWA	1210 mg/m <sup>3</sup> ; 500 ppm
Ireland: 8 hours	1210 mg/m <sup>3</sup> ; 500 ppm IOELV

DNEL/DMEL: DNEL Long-term, workers, dermal: 186 mg/kg bw/d.  
DNEL Short-term, workers, inhalative: 2,420 mg/m<sup>3</sup>  
DNEL Long-term, workers, inhalative: 1,210 mg/m<sup>3</sup>  
DNEL Long-term, consumers, oral: 62 mg/kg bw/d.  
DNEL Long-term, consumers, dermal: 62 mg/kg bw/d.  
DNEL Long-term, consumers, inhalative: 200 mg/m<sup>3</sup>

PNEC: PNEC water (freshwater): 10.6 mg/L.  
PNEC water (marine water): 1.06 mg/L.  
PNEC water (intermittent release): 21 mg/L.  
PNEC sediment (freshwater): 30.4 mg/kg dwt.  
PNEC sediment (marine water): 3.04 mg/kg dwt.  
PNEC soil: 33.3 mg/kg dwt.  
PNEC sewage treatment plant: 100 mg/L.

### 8.2 Exposure controls

Explosion protection required. Provide good ventilation and/or an exhaust system in the work area.

### Personal protection equipment

#### Occupational exposure controls

All information for relevant exposure scenarios including operational conditions and risk management measures are listed in 'Annex II: worker exposure and risk assessment'.

Respiratory protection: Use filter type AX (= against vapours of low boiling organic substances) according to EN 14387.  
Have a breathing apparatus that is not dependent on the circulating air ready for emergencies.

Hand protection: Protective gloves according to EN 374.  
Glove material: Butyl caoutchouc (butyl rubber) - Layer thickness  $\geq$  0.5 mm.  
Breakthrough time:  $>$ 480 min.  
Observe glove manufacturer's instructions concerning penetrability and breakthrough time.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 7 of 121

Eye protection: Tightly sealed goggles according to EN 166.  
Body protection: Use solvent-resistant protective clothing.  
Recommendation: Flame-retardant protective clothing, antistatic.  
safety shoes according to EN 345-347.

General protection and hygiene measures:

Keep away from heat sources, sparks and open flames. Take precautionary measures against static discharges.  
Avoid contact with skin and eyes.  
When using do not eat, drink or smoke.  
Wash hands before breaks and after work.  
Have eye wash bottle or eye rinse ready at work place.

Alternatives to the personal protective measures as mentioned can only be determined in agreement with a responsible safety expert.

### Consumer exposure controls

All information for relevant exposure scenarios including operational conditions and risk management measures are listed in 'Annex II: consumer exposure and risk assessment'.

### Environmental exposure controls

All information for relevant exposure scenarios including operational conditions and risk management measures are listed in 'Annex III: Environmental Exposure and Risk Assessment and Annex IV: Environmental Exposure Calculation Tool'.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Appearance: Form: liquid  
Colour: colourless, clear

Odour: sweet, aromatic  
Odour threshold: 47.5 mg/m<sup>3</sup>

pH value: at 10 g/L: neutral; 50% in H<sub>2</sub>O: 5-6

Melting point/freezing point: -94.7 °C  
Initial boiling point and boiling range: 56.05 °C  
Flash point/flash point range: -17 °C (c.c.)  
Evaporation rate: No data available

Flammability: Highly flammable liquid and vapour.  
Explosion limits: LEL (Lower Explosion Limit): 2.50 Vol-%  
UEL (Upper Explosive Limit): 14.30 Vol-%

Vapour pressure: at 20 °C: 240 hPa  
at 50 °C: 800 hPa

Vapour density: 2.1  
Density: at 20 °C: 0.79 g/mL

Solubility: at 20 °C: in organic solvents 100 %  
Water solubility: at 20 °C: multimiscible

Partition coefficient: n-octanol/water: -0.24 log P(o/w)  
Based on the n-octanol/water partition coefficient accumulation in organisms is not expected.

Auto-ignition temperature: 465 °C (Inflammation group G1)  
Decomposition temperature: none

Viscosity, dynamic: at 20 °C: 0.32 mPa\*s

Explosive properties: Explosion category 1; Explosion group II A  
Oxidizing characteristics: Highly flammable liquid and vapour.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 8 of 121

### 9.2 Other information

Ignition temperature: 465 °C (Inflammation group G1)  
Refraction index: at 20 °C: 1.358 - 1.359  
Additional information: Molar mass: 58.09 g/mol  
Dissociation constant: pKa = 24.2 at 25°C  
Evaporation rate: 2.0 (ether = 1)  
Evaporation rate: 5.6 (n-BuAc = 1)  
Saturation concentration at 20 °C: 550 g/m<sup>3</sup>

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Acetone reacts in presence of bases.  
Vapours form potentially explosive mixtures with air. Heavier than air, they proceed at floor level and may backflash over great distances when ignited. May become electrostatically charged.

### 10.2 Chemical stability

Product is stable under normal storage conditions.

### 10.3 Possibility of hazardous reactions

No hazardous reactions known.

### 10.4 Conditions to avoid

Highly flammable. Concentrated vapours are heavier than air.  
Take precautionary measures against static discharges.  
Forms explosive mixtures with air, also in empty, uncleaned containers.  
May produce, when being mixed with chloridized hydrocarbons and exposed to light, strongly irritating chloric acetone.

### 10.5 Incompatible materials

Attacks many plastics and rubbers. On contact with barium hydroxide, sodium hydroxide and many other alkaline materials condensation may occur.  
Avoid contact with strong oxidizing agents, alkalis and amines.

### 10.6 Hazardous decomposition products

In case of fire may be liberated: Carbon monoxide and carbon dioxide.

Thermal decomposition: none

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Acute toxicity: LD50 Rat, oral: 5800 mg/kg bw (OECD 401)  
LD50 Rat, dermal: > 15800 mg/kg bw  
LC50 Rat, inhalative: 76 mg/L/4h



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 9 of 121

Toxicological effects: Acute toxicity (oral): Based on available data, the classification criteria are not met.  
Acute toxicity (dermal): Based on available data, the classification criteria are not met.  
Acute toxicity (inhalative): Based on available data, the classification criteria are not met.  
Skin corrosion/irritation: Based on available data, the classification criteria are not met.  
Specific symptoms in animal studies (guinea pig): Does not cause irritation.  
Serious eye damage/irritation: Eye Irrit. 2; H319 = Causes serious eye irritation.  
Specific symptoms in animal studies (Rabbit): irritant (OECD 405)  
Sensitisation to the respiratory tract: Based on available data, the classification criteria are not met.  
Skin sensitisation: Based on available data, the classification criteria are not met.  
Sensitisation: Specific symptoms in animal studies (guinea pig): not sensitising (OECD 406)  
Germ cell mutagenicity/Genotoxicity: Based on available data, the classification criteria are not met.  
not mutagenic in bacterial mutagenicity (OECD 471 )  
Chromosomal aberrations, in-vitro (OECD 473): negative  
Gene-mutations mammalian cells, in-vitro (OECD 476): negative  
Micronucleus test in-vivo Mouse/hamster (non-Guideline): negative  
Carcinogenicity: Based on available data, the classification criteria are not met.  
Not carcinogen at long term exposure (Mouse, dermal).  
Reproductive toxicity: Based on available data, the classification criteria are not met.  
Effects on fertility: No impairment of reproductive performance in animal experiments.  
developmental toxicity: None developmental toxicity (inhalation at Rat, Mouse, OECD 414).  
Effects on or via lactation: Lack of data.  
Specific target organ toxicity (single exposure): STOT SE 3; H336 = May cause drowsiness or dizziness. May cause drowsiness or dizziness.  
Specific target organ toxicity (repeated exposure): Based on available data, the classification criteria are not met.  
NOAEL Rat, oral: 900 mg/kg/90d bw/d  
NOAEC Rat, inhalative: 22500 mg/m<sup>3</sup>/8w  
Aspiration hazard: Based on available data, the classification criteria are not met.

Other information: Short term effect: 10000 ppm were well-tolerated.  
No symptoms did appear after 30 to 60 minutes.

## Symptoms

Burning eyes and skin. fatigue, nausea, Headache, dizziness, unconsciousness.  
In case of inhalation:  
For the development of any overt signs of toxicity in humans, accidental exposures to extremely large amounts of acetone by inhalation of vapour or ingestion of liquid are necessary (e. g. several thousand ppm of acetone vapour).  
In case of ingestion: Gastric and intestinal problems.  
After contact with skin:  
Irritant. Repeated exposure may cause skin dryness or cracking, due to defatting properties.  
No indication for sensitising properties in humans.  
After eye contact: Causes serious eye irritation.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 10 of 121

## SECTION 12: Ecological information

### 12.1 Toxicity

Aquatic toxicity:

Acute effects:

Fish toxicity:

- freshwater species: 96h LC50 (Oncorhynchus mykiss): 5,540 mg/L
- marine species: 96h LC50 (Alburnus alburnus (alburnum)): 11,000 mg/L

Invertebrate toxicity:

- freshwater species: 48h EC50 (Daphnia pulex (water flea)): 8,800 mg/L
- marine species: 24h EC50 (Artemisia salina): 2,100 mg/l

Algae toxicity:

- freshwater species: 8h NOEC (Microcystis aeruginosa): 530 mg/L/8 d.
- marine species: 96h NOEC (Prorocentrum minimum): 430 mg/L

Bacterial toxicity:

EC 12: (30 min; activated sludge; OECD 209): 1,000 mg/L

Long-term effects:

Long-term toxicity to aquatic invertebrates:

28-days NOEC (Daphnia pulex (water flea); reproduction): 2,212 mg/L

No information on long-term effects of fish and algae available.

Long-term effects on aquatic organisms are not relevant due to the rapid elimination in water.

### 12.2 Persistence and degradability

Further details:

Abiotic degradation:

DT50, 19 - 114 d (Air, Indirect photodegradation by reaction with OH radicals.)

Abiotic degradation: none (Water, hydrolysis)

Biodegradation: 91 %/28 d (OECD 301B).

ThOD 84 %/5 d. (BOD5, APHA 219).

COD: 2.21 g O<sub>2</sub>/g

Product is readily biodegradable.

Effects in sewage plants: In activated sludge: 100 %/ 4 d (anaerobic conditions; Warburg Respirometer)

### 12.3 Bioaccumulative potential

Bioconcentration factor (BCF):

3 (calculated, BCFWIN v2.17)

### 12.4 Mobility in soil

Adsorption coefficient soil (K<sub>d</sub>) : 1.5 L/kg, at 20 °C.

The soil sorption coefficient indicates that acetone is mobile in soil and may be transported by soil water.

Volatility:

Henry constant: 2.929 - 3.070 Pa·m<sup>3</sup>/mol (25 °C water).

Henry constant: 3.311 Pa·m<sup>3</sup>/mol (25 °C marine water).

Experimentally determined Henry's Law constants indicate a moderate volatility from water.

### 12.5 Results of PBT and vPvB assessment

This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 11 of 121

### 12.6 Other adverse effects

General information: Terrestrial toxicity:  
48h LD50 (*Eisenia fetida*): 0.1 - 1 mg/cm<sup>3</sup>  
48h LD50 (*Ambystoma mexicanum*): 20,000 mg/L  
48h LD50 (*Xenopus laevis*): 24,000 mg/L  
In a study conducted according to OECD Guideline 207 (Earthworm, Acute Toxicity Tests: filter paper contact test), acetone showed a moderate toxicity to *Eisenia fetida*. In further short term toxicity studies, *Ambystoma mexicanum* and *Xenopus laevis* larvae exposed to acetone under static conditions in covered glass basins showed 48h LC50 values of 20,000 mg/L and 24,000 mg/L, respectively.  
Do not allow to enter into ground-water, surface water or drains.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Product

Waste key number: 07 01 04\* = Wastes from the manufacture, formulation, supply and use (MFSU) of basic organic chemicals: organic solvents, halogen-free  
\* = Evidence for disposal must be provided.

Recommendation: Incinerate as hazardous waste according to applicable local, state, and federal regulations.  
Do not dispose of with household waste.

#### Contaminated packaging

Recommendation: Dispose of waste according to applicable legislation.  
Handle contaminated packages in the same way as the substance itself.  
Non-contaminated packages may be recycled.

## SECTION 14: Transport information

### 14.1 UN number

ADR/RID, IMDG, IATA-DGR:  
UN 1090

### 14.2 UN proper shipping name

ADR/RID, IMDG, IATA-DGR:  
UN 1090, ACETONE

### 14.3 Transport hazard class(es)

ADR/RID: Class 3, Code: F1  
IMDG: Class 3, Subrisk -  
IATA-DGR: Class 3

### 14.4 Packing group

ADR/RID, IMDG, IATA-DGR:  
II

### 14.5 Environmental hazards

Marine pollutant: no



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 12 of 121

### 14.6 Special precautions for user

#### Land transport (ADR/RID)

Warning board: ADR/RID: Kemmler-number 33, UN number UN 1090  
Hazard label: 3  
Limited quantities: 1 L  
EQ: E2  
Contaminated packaging - Instructions: P001 IBC02 R001  
Special provisions for packing together: MP19  
Portable tanks - Instructions: T4  
Portable tanks - Special provisions: TP1  
Tank coding: LGBF  
Tunnel restriction code: D/E

#### Sea transport (IMDG)

EmS: F-E, S-D  
Special provisions: -  
Limited quantities: 1 L  
Excepted quantities: E2  
Contaminated packaging - Instructions: P001  
Contaminated packaging - Provisions: -  
IBC - Instructions: IBC02  
IBC - Provisions: -  
Tank instructions - IMO: -  
Tank instructions - UN: T4  
Tank instructions - Provisions: TP1  
Stowage and handling: Category E.  
Properties and observations: Colourless, clear liquid, with a characteristic mint-like odour. Flashpoint: -20°C to -18°C c.c. Explosive limits: 2.5% to 13%. Miscible with water.  
Segregation group: none

#### Air transport (IATA)

Hazard label: Flamm. liquid  
Excepted Quantity Code: E2  
Passenger and Cargo Aircraft: Ltd.Qty.: Pack.Instr. Y341 - Max. Net Qty/Pkg. 1 L  
Passenger and Cargo Aircraft: Pack.Instr. 353 - Max. Net Qty/Pkg. 5 L  
Cargo Aircraft only: Pack.Instr. 364 - Max. Net Qty/Pkg. 60 L  
Emergency Response Guide-Code (ERG): 3H

### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Pollution category: Z  
Vessel type: -  
Product name: Acetone

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### National regulations - Great Britain

Hazchem-Code: •2YE  
No data available

#### National regulations - EC member states

Volatile organic compounds (VOC):  
100 % by weight = 790 g/L

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 13 of 121

Further regulations, limitations and legal requirements:

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive] P5c Use restriction according to REACH annex XVII, no.: 40

The placing on the market and the use of the substance is not permitted in decorative articles, games and fun games.

### 15.2 Chemical Safety Assessment

For this substance a chemical safety assessment has been carried out.

## SECTION 16: Other information

### Further information

Literature: REACH Registration Dossier Acetone. P&D-REACH Consortium, 2010.  
ICSC 0087

Reason of change: Changes in section 15: Provisions  
Date of first version: 19/11/2010

### Department issuing data sheet

Contact person: see section 1: Dept. responsible for information

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 14 of 121

### Exposure Scenario 0: Generic exposure scenario (GES): Industrial Processes relevant for Acetone containing products (ES 1 - 11)

#### List of use descriptors

Sector of uses [SU]: SU3: Industrial uses

#### Application

Activities and processes: Generic exposure scenario, applies to all contributing exposure scenarios related to exposure scenario 1 - 11: industrial uses

- ES1 - Manufacture, processing and distribution of substances and mixtures
- ES2 - Use in laboratories
- ES3 - Uses in coatings
- ES4 - Use in binders and release agents
- ES5 - Rubber production and processing
- ES6 - Polymer manufacturing
- ES7 - Polymer processing
- ES8 - Use in cleaning agents
- ES9 - Use in oil and gas field drilling and production operations
- ES10 - Blowing agents
- ES11 - Mining chemicals

Contributing Scenarios:	1	Use in closed process, no likelihood of exposure General exposures (closed systems) (worker)	Page 15
	2	Use in closed, continuous process with occasional controlled exposure General exposures (closed systems) (worker)	Page 15
	3	Use in closed batch process (synthesis or formulation) General exposures (closed systems) (worker)	Page 16
	4	Use in batch and other process (synthesis) where opportunity for exposure arises Process sampling (open systems) (worker)	Page 16
	5	Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact) Mixing operations (open systems) (worker)	Page 17
	6	Calendering operations Calendering (including Banburys) (worker)	Page 17
	7	Industrial spraying Spraying/fogging by machine application (worker)	Page 17
	8	Industrial spraying Spraying/fogging by machine application (worker)	Page 18
	9	Industrial spraying Spraying/fogging by machine application (worker)	Page 18
	10	Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities Bulk transfers (worker)	Page 19
	11	Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities Bulk transfers (worker)	Page 19
	12	Transfer of substance or preparation into small containers (dedicated filling line, including weighing) Small package filling (worker)	Page 20
	13	Roller application or brushing Rolling, Brushing (worker)	Page 20
	14	Roller application or brushing Equipment cleaning and maintenance (worker)	Page 20
	15	Use of blow agents in manufacture of foam Foaming (worker)	Page 21

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 15 of 121

Contributing Scenarios:	16	Treatment of articles by dipping and pouring Dipping, immersion and pouring (worker)	Page 21
	17	Production of preparations or articles by tableting, compression, extrusion, pelletisation (worker)	Page 22
	18	Use in laboratory reagents (small scale) Laboratory activities (worker)	Page 22
	19	Hand-mixing with intimate contact and only PPE available Hand application - Finger paints, pastels (worker)	Page 22

Contributing exposure scenario 1

### Use in closed process, no likelihood of exposure General exposures (closed systems) (worker)

#### List of use descriptors

Process categories [PROC]:

PROC1: Use in closed process, no likelihood of exposure

#### Exposure prediction

Exposure estimation and reference to its source:

inhalative: 0.01 ppm  
dermal: 0.34 mg/kg/d

Risk characterisation ratio (RCR):

RCR: 0.002  
inhalative: 0.00002  
dermal: 0.002  
all relevant routes: 0.002

#### Risk management measures

Technical conditions and measures at process level (source) to prevent release:

Sample via a closed loop or other system to avoid exposure. Handle substance within a closed system.

Operational conditions and risk management measures:

(closed systems); Process sampling

Conditions and measures related to personal protection, hygiene and health evaluation:

Use personal protective equipment as required.

Contributing exposure scenario 2

### Use in closed, continuous process with occasional controlled exposure General exposures (closed systems) (worker)

#### List of use descriptors

Process categories [PROC]:

PROC2: Use in closed, continuous process with occasional controlled exposure

#### Exposure prediction

Exposure estimation and reference to its source:

inhalative: 50 ppm  
dermal: 1.37 mg/kg/d

Risk characterisation ratio (RCR):

RCR: 0.11  
inhalative: 0.10  
dermal: 0.01  
all relevant routes: 0.11

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 16 of 121

### Risk management measures

Technical conditions and measures at process level (source) to prevent release:

Sample via a closed loop or other system to avoid exposure. Handle substance within a closed system.

Operational conditions and risk management measures:

Continuous process, Process sampling

Conditions and measures related to personal protection, hygiene and health evaluation:

Use personal protective equipment as required.

Contributing exposure scenario 3

### Use in closed batch process (synthesis or formulation)

#### General exposures (closed systems) (worker)

#### List of use descriptors

Process categories [PROC]:

PROC3: Use in closed batch process (synthesis or formulation)

### Exposure prediction

Exposure estimation and reference to its source:

inhalative: 100 ppm

dermal: 0.34 mg/kg/d

Risk characterisation ratio (RCR):

RCR: 0.2

inhalative: 0.20

dermal: 0.002

all relevant routes: 0.20

### Risk management measures

Technical conditions and measures at process level (source) to prevent release:

Sample via a closed loop or other system to avoid exposure. Handle substance within a closed system.

Operational conditions and risk management measures:

Batch process, Process sampling

Conditions and measures related to personal protection, hygiene and health evaluation:

Use personal protective equipment as required.

Contributing exposure scenario 4

### Use in batch and other process (synthesis) where opportunity for exposure arises

#### Process sampling (open systems) (worker)

#### List of use descriptors

Process categories [PROC]:

PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises

### Exposure prediction

Exposure estimation and reference to its source:

inhalative: 100 ppm

dermal: 6.86 mg/kg/d

Risk characterisation ratio (RCR):

RCR: 0.24

inhalative: 0.20

dermal: 0.04

all relevant routes: 0.24

### Risk management measures

Conditions and measures related to personal protection, hygiene and health evaluation:

Use personal protective equipment as required.



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 17 of 121

Contributing exposure scenario 5

### Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)

#### Mixing operations (open systems) (worker)

##### List of use descriptors

Process categories [PROC]:

PROC5: Mixing or blending in batch processes

##### Exposure prediction

Exposure estimation and reference to its source:

inhalative: 250 ppm  
dermal: 13.71 mg/kg/d

Risk characterisation ratio (RCR):

RCR: 0.57  
inhalative: 0.50  
dermal: 0.07  
all relevant routes: 0.57

##### Risk management measures

Operational conditions and risk management measures:

Batch process, Process sampling

Conditions and measures related to personal protection, hygiene and health evaluation:

Use personal protective equipment as required.

Contributing exposure scenario 6

### Calendering operations

#### Calendering (including Banburys) (worker)

##### List of use descriptors

Process categories [PROC]:

PROC6: Calendering operations

##### Exposure prediction

Exposure estimation and reference to its source:

inhalative: 250 ppm  
dermal: 27.43 mg/kg/d

Risk characterisation ratio (RCR):

RCR: 0.65  
inhalative: 0.50  
dermal: 0.15  
all relevant routes: 0.65

##### Risk management measures

Conditions and measures related to personal protection, hygiene and health evaluation:

Use personal protective equipment as required.

Contributing exposure scenario 7

### Industrial spraying

#### Spraying/fogging by machine application (worker)

##### List of use descriptors

Process categories [PROC]:

PROC7: Industrial spraying

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 18 of 121

### Exposure prediction

Exposure estimation and reference to its source:

inhalative: 25 ppm (with local exhaust ventilation, efficiency of 95%)  
dermal: 2.14 mg/kg/d (with local exhaust ventilation, efficiency of 95%)

Risk characterisation ratio (RCR):

RCR: 0.06  
inhalative: 0.05  
dermal: 0.01  
all relevant routes: 0.06

### Risk management measures

Technical conditions and measures at process level (source) to prevent release:

Ensure material transfers are under containment or extract ventilation.

Operational conditions and risk management measures:

with local exhaust ventilation

Conditions and measures related to personal protection, hygiene and health evaluation:

Use personal protective equipment as required.

Contributing exposure scenario 8

### Industrial spraying

#### Spraying/fogging by machine application (worker)

#### List of use descriptors

Process categories [PROC]:

PROC7: Industrial spraying

### Exposure prediction

Exposure estimation and reference to its source:

inhalative: 350 ppm (dilution ventilation effectiveness 30 %)  
dermal: 42.86 mg/kg/d

Risk characterisation ratio (RCR):

RCR: 0.93  
inhalative: 0.70  
dermal: 0.23  
all relevant routes: 0.93

### Risk management measures

Technical conditions and measures at process level (source) to prevent release:

Ensure operation is undertaken outdoors.

Conditions and measures related to personal protection, hygiene and health evaluation:

Use personal protective equipment as required.

Contributing exposure scenario 9

### Industrial spraying

#### Spraying/fogging by machine application (worker)

#### List of use descriptors

Process categories [PROC]:

PROC7: Industrial spraying

### Exposure prediction

Exposure estimation and reference to its source:

inhalative: 50 ppm (Respiratory protective device, efficiency of 90%)  
dermal: 42.86 mg/kg/d

Risk characterisation ratio (RCR):

RCR: 0.33  
inhalative: 0.10  
dermal: 0.23  
all relevant routes: 0.33

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 19 of 121

### Risk management measures

Conditions and measures related to personal protection, hygiene and health evaluation:

Wear a respirator conforming to EN140 with Type A filter or better.

Contributing exposure scenario 10

### Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

#### Bulk transfers (worker)

#### List of use descriptors

Process categories [PROC]:

PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

### Exposure prediction

Exposure estimation and reference to its source:

inhalative: 250 ppm  
dermal: 13.71 mg/kg/d

Risk characterisation ratio (RCR):

RCR: 0.57  
inhalative: 0.50  
dermal: 0.07  
all relevant routes: 0.57

### Risk management measures

Operational conditions and risk management measures:

Non-dedicated facility, transfer from/pouring from containers

Conditions and measures related to personal protection, hygiene and health evaluation:

Use personal protective equipment as required.

Contributing exposure scenario 11

### Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

#### Bulk transfers (worker)

#### List of use descriptors

Process categories [PROC]:

PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

### Exposure prediction

Exposure estimation and reference to its source:

inhalative: 150 ppm  
dermal: 6.86 mg/kg/d

Risk characterisation ratio (RCR):

RCR: 0.34  
inhalative: 0.30  
dermal: 0.037  
all relevant routes: 0.34

### Risk management measures

Operational conditions and risk management measures:

Dedicated facility, transfer from/pouring from containers

Conditions and measures related to personal protection, hygiene and health evaluation:

Use personal protective equipment as required.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 20 of 121

Contributing exposure scenario 12

### **Transfer of substance or preparation into small containers (dedicated filling line, including weighing)**

#### **Small package filling (worker)**

#### **List of use descriptors**

Process categories [PROC]:

PROC9: Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

#### **Exposure prediction**

Exposure estimation and reference to its source:

inhalative: 200 ppm

dermal: 6.86 mg/kg/d

Risk characterisation ratio (RCR):

RCR: 0.44

inhalative: 0.40

dermal: 0.04

all relevant routes: 0.44

#### **Risk management measures**

Operational conditions and risk management measures:

Dedicated facility, pouring from small containers

Conditions and measures related to personal protection, hygiene and health evaluation:

Use personal protective equipment as required.

Contributing exposure scenario 13

### **Roller application or brushing**

#### **Rolling, Brushing (worker)**

#### **List of use descriptors**

Process categories [PROC]:

PROC10: Roller application or brushing

#### **Exposure prediction**

Exposure estimation and reference to its source:

inhalative: 250 ppm

dermal: 27.43 mg/kg/d

Risk characterisation ratio (RCR):

RCR: 0.65

inhalative: 0.50

dermal: 0.15

all relevant routes: 0.65

#### **Risk management measures**

Operational conditions and risk management measures:

Or: Equipment cleaning and maintenance

Conditions and measures related to personal protection, hygiene and health evaluation:

Use personal protective equipment as required.

Contributing exposure scenario 14

### **Roller application or brushing**

#### **Equipment cleaning and maintenance (worker)**

#### **List of use descriptors**

Process categories [PROC]:

PROC10: Roller application or brushing

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 21 of 121

### Exposure prediction

Exposure estimation and reference to its source:

inhalative: 250 ppm  
dermal: 27.43 mg/kg/d

Risk characterisation ratio (RCR):

RCR: 0.65  
inhalative: 0.50  
dermal: 0.15  
all relevant routes: 0.65

### Risk management measures

Conditions and measures related to personal protection, hygiene and health evaluation:

Use personal protective equipment as required.

Contributing exposure scenario 15

## Use of blow agents in manufacture of foam Foaming (worker)

### List of use descriptors

Process categories [PROC]:

PROC12: Use of blowing agents in manufacture of foam

### Exposure prediction

Exposure estimation and reference to its source:

inhalative: 100 ppm  
dermal: 0.34 mg/kg/d

Risk characterisation ratio (RCR):

RCR: 0.2  
inhalative: 0.20  
dermal: 0.00  
all relevant routes: 0.20

### Risk management measures

Operational conditions and risk management measures:

Production of foam-based objects

Conditions and measures related to personal protection, hygiene and health evaluation:

Use personal protective equipment as required.

Contributing exposure scenario 16

## Treatment of articles by dipping and pouring Dipping, immersion and pouring (worker)

### List of use descriptors

Process categories [PROC]:

PROC13: Treatment of articles by dipping and pouring

### Exposure prediction

Exposure estimation and reference to its source:

inhalative: 250 ppm  
dermal: 13.71 mg/kg/d

Risk characterisation ratio (RCR):

RCR: 0.57  
inhalative: 0.50  
dermal: 0.074  
all relevant routes: 0.57

### Risk management measures

Conditions and measures related to personal protection, hygiene and health evaluation:

Use personal protective equipment as required.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 22 of 121

Contributing exposure scenario 17

### **Production of preparations or articles by tableting, compression, extrusion, pelletisation (worker)**

#### **List of use descriptors**

Process categories [PROC]:

PROC14: Production of preparations or articles by tableting, compression, extrusion, pelletisation

#### **Exposure prediction**

Exposure estimation and reference to its source:

inhalative: 50 ppm  
dermal: 0.34 mg/kg/d

Risk characterisation ratio (RCR):

RCR: 0.1  
inhalative: 0.10  
dermal: 0.00  
all relevant routes: 0.10

#### **Risk management measures**

Conditions and measures related to personal protection, hygiene and health evaluation:

Use personal protective equipment as required.

Contributing exposure scenario 18

### **Use in laboratory reagents (small scale) Laboratory activities (worker)**

#### **List of use descriptors**

Process categories [PROC]:

PROC15: Use as laboratory reagent

#### **Exposure prediction**

Exposure estimation and reference to its source:

inhalative: 50 ppm  
dermal: 0.34 mg/kg/d

Risk characterisation ratio (RCR):

RCR: 0.1  
inhalative: 0.10  
dermal: 0.00  
all relevant routes: 0.10

#### **Risk management measures**

Conditions and measures related to personal protection, hygiene and health evaluation:

Use personal protective equipment as required.

Contributing exposure scenario 19

### **Hand-mixing with intimate contact and only PPE available Hand application - Finger paints, pastels (worker)**

#### **List of use descriptors**

Process categories [PROC]:

PROC19: Hand-mixing with intimate contact and only PPE available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 23 of 121

### Exposure prediction

Exposure estimation and reference to its source:

inhalative: 250 ppm

dermal: 28.29 mg/kg/d (Gloves, efficiency of 80%)

Risk characterisation ratio (RCR):

RCR: 0.65

inhalative: 0.50

dermal: 0.15

all relevant routes: 0.65

### Risk management measures

Conditions and measures related to personal protection, hygiene and health evaluation:

Wear suitable gloves tested to EN374.

### Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

Exposure assessment and method: Shown are the result of the quantitative exposure and risk assessment prepared based on the 'GES Worker Chemical Safety Assessment (CSA) Template'. This tool can be downloaded from the CEFIC website:  
<http://cefic.org/templates/shwPublications.asp?HID=750>

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 24 of 121

### Exposure Scenario 1: Manufacture, processing and distribution of substances and mixtures \*

#### List of use descriptors

Sector of uses [SU]: SU3: Industrial uses

#### Application

Activities and processes: Manufacture, Processing, Composition, Distribution.  
Includes recycling/recovery, material transfers, storage, maintenance and loading (including marine vessel/barge, road/rail car and bulk container), sampling and associated laboratory activities.

\* Examples for processing:

use as an intermediate,

use as a monomer etc.,

use as a solvent,

use for the manufacturing of resins

Remark:

Process categories [PROC]

PROC1, PROC2, PROC3, PROC4, PROC5, PROC6, PROC8a, PROC8b, PROC9, PROC10, PROC14, PROC15

Control of worker exposure:

See section risk management measures

Human Health, Worker exposure and risk assessment:

Exposure assessment and method: Shown are the result of the quantitative exposure and risk assessment prepared based on the 'GES Worker Chemical Safety Assessment (CSA) Template'. This tool can be downloaded from the CEFIC website:

<http://cefic.org/templates/shwPublications.asp?HID=750>

Examples for Environmental release categories [ERC]:

ERC1, ERC2, ERC4, ERC6a

Environment, ECT acetone:

Please use the 'ECT Acetone' to check your local conditions. The Excel-tool enables the performance of scaling calculation for specific local environmental conditions. It can be downloaded from the web page of the Phenol & Derivatives REACH-consortium:

<http://www.reachcentrum.eu/EN/consortium-management/consortia-under-reach/phenol-derivatives-reach-consortium.aspx>

Guidance to check compliance with the exposure scenario: Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Contributing Scenarios:	1	General information Applies to all contributing exposure scenarios related to exposure scenario 1: Manufacture, processing and distribution of substances and mixtures (environment)	Page 25
	2	General information Applies to all contributing exposure scenarios related to exposure scenario 1: Manufacture, processing and distribution of substances and mixtures (worker)	Page 26



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 25 of 121

Contributing exposure scenario 1

### General information

**Applies to all contributing exposure scenarios related to exposure scenario 1:  
Manufacture, processing and distribution of substances and mixtures (environment)**

### List of use descriptors

Environmental release categories [ERC]:

- ERC1: Manufacture of the substance
- ERC2: Formulation into mixture
- ERC4: Use of non-reactive processing aid at industrial site (no inclusion into or onto article)
- ERC6a: Use of intermediate

### Operational conditions

Product characteristics: Substance is a unique structure, ketone, readily biodegradable

Amounts used:

Annual site tonnage Please use the Excel-Tool 'ECT Acetone' to calculate your maximum tonnage/year.

Duration and frequency of use:

360 d/y

Other relevant operational conditions:

Indoor/Outdoor use

### Exposure prediction

Exposure estimation and reference to its source:

Common practices vary across sites thus conservative process release estimates used. Please use the 'ECT Acetone' to check your local conditions.

Risk characterisation ratio (RCR):

ECT Acetone

### Risk management measures

Technical conditions and measures at process level (source) to prevent release:

Common practices vary across sites thus conservative process release estimates used. Typical technical measures are closed systems or scrubbers or charcoal adsorbers. Treat air emission to provide a typical removal efficiency of (%): 90

### Disposal considerations

Conditions and measures related to sewage treatment plant:

Please use the Excel-Tool 'ECT Acetone' to check your local conditions.

Conditions and measures related to external treatment of waste for disposal:

External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste:

External treatment and disposal of waste should comply with applicable local and/or national regulations.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 26 of 121

Contributing exposure scenario 2

### General information

**Applies to all contributing exposure scenarios related to exposure scenario 1:  
Manufacture, processing and distribution of substances and mixtures (worker)**

### List of use descriptors

Process categories [PROC]:

- PROC1: Use in closed process, no likelihood of exposure
- PROC2: Use in closed, continuous process with occasional controlled exposure
- PROC3: Use in closed batch process (synthesis or formulation)
- PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises
- PROC5: Mixing or blending in batch processes
- PROC6: Calendering operations
- PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities
- PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities
- PROC9: Transfer of substance or mixture into small containers (dedicated filling line, including weighing)
- PROC10: Roller application or brushing
- PROC14: Production of preparations or articles by tableting, compression, extrusion, pelletisation
- PROC15: Use as laboratory reagent

### Operational conditions

Product characteristics: liquid, vapour pressure > 10 kPa

Concentration of the substance in a mixture:

Covers percentage substance in the product up to 100 % (unless stated differently).

Duration and frequency of use:

Covers daily exposures up to 8h (unless stated differently).

Other relevant operational conditions:

Assumes a good basic standard of occupational hygiene is implemented.

### Exposure prediction

Exposure estimation and reference to its source:

refer to GES No. 0 industrial

Risk characterisation ratio (RCR):

refer to GES No. 0 industrial

### Risk management measures

Technical conditions and measures at process level (source) to prevent release:

Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan.

Operational conditions and risk management measures:

Locate bulk storage outdoors.

Conditions and measures related to personal protection, hygiene and health evaluation:

Use suitable eye protection.

If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to EN374 and provide employee skin care programmes.

### Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

'ECT Acetone': The Excel-tool enables the performance of scaling calculation for specific local environmental conditions. It can be downloaded from the web page of the Phenol & Derivatives REACH-consortium:  
<http://www.reachcentrum.eu/EN/consortium-management/consortia-under-reach/phenol-derivatives-reach-consortium.aspx>

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 27 of 121

### Exposure Scenario 2: Use in laboratories

#### List of use descriptors

Sector of uses [SU]: SU3: Industrial uses

#### Application

Activities and processes: use of the substance within laboratory settings, including material transfers and equipment cleaning

Remark: Process categories [PROC]  
PROC10, PROC15  
Process Categories (additionally): PROC19

Control of worker exposure:  
See section risk management measures

Human Health, Worker exposure and risk assessment:  
Exposure assessment and method: Shown are the result of the quantitative exposure and risk assessment prepared based on the 'GES Worker Chemical Safety Assessment (CSA) Template'. This tool can be downloaded from the CEFIC website:  
<http://cefic.org/templates/shwPublications.asp?HID=750>

Examples for Environmental release categories [ERC]:  
ERC4

Environment, ECT acetone:  
Please use the 'ECT Acetone' to check your local conditions. The Excel-tool enables the performance of scaling calculation for specific local environmental conditions. It can be downloaded from the web page of the Phenol & Derivatives REACH-consortium:  
<http://www.reachcentrum.eu/EN/consortium-management/consortia-under-reach/phenol-derivatives-reach-consortium.aspx>

Guidance to check compliance with the exposure scenario: Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Contributing Scenarios:	1	General information Applies to all contributing exposure scenarios related to exposure scenario 2: Use in laboratories (environment)	Page 27
	2	General information Applies to all contributing exposure scenarios related to exposure scenario 2: Use in laboratories (worker)	Page 28

Contributing exposure scenario 1

#### General information

**Applies to all contributing exposure scenarios related to exposure scenario 2: Use in laboratories (environment)**

#### List of use descriptors

Environmental release categories [ERC]:

ERC4: Use of non-reactive processing aid at industrial site (no inclusion into or onto article)

#### Operational conditions

Product characteristics: Substance is a unique structure, ketone, readily biodegradable  
Amounts used:  
Annual site tonnage Please use the Excel-Tool 'ECT Acetone' to calculate your maximum tonnage/year.

Duration and frequency of use:  
360 d/y

Other relevant operational conditions:  
Indoor/Outdoor use

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 28 of 121

### Exposure prediction

Exposure estimation and reference to its source:

Common practices vary across sites thus conservative process release estimates used.  
Please use the 'ECT Acetone' to check your local conditions.

Risk characterisation ratio (RCR):

ECT Acetone

### Risk management measures

Technical conditions and measures at process level (source) to prevent release:

Common practices vary across sites thus conservative process release estimates used.  
Typical technical measures are closed systems or scrubbers or charcoal adsorbers.  
Treat air emission to provide a typical removal efficiency of (%): 90 %

### Disposal considerations

Conditions and measures related to sewage treatment plant:

Please use the Excel-Tool 'ECT Acetone' to check your local conditions.

Conditions and measures related to external treatment of waste for disposal:

External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste:

External treatment and disposal of waste should comply with applicable local and/or national regulations.

Contributing exposure scenario 2

### General information

**Applies to all contributing exposure scenarios related to exposure scenario 2: Use in laboratories (worker)**

### List of use descriptors

Process categories [PROC]:

PROC10: Roller application or brushing

PROC15: Use as laboratory reagent

PROC19: Hand-mixing with intimate contact and only PPE available

### Operational conditions

Product characteristics: liquid, vapour pressure > 10 kPa

Concentration of the substance in a mixture:

Covers percentage substance in the product up to 100 % (unless stated differently.)

Duration and frequency of use:

Covers daily exposures up to 8h

Other relevant operational conditions:

Assumes a good basic standard of occupational hygiene is implemented.

### Exposure prediction

Exposure estimation and reference to its source:

refer to GES No. 0 industrial

Risk characterisation ratio (RCR):

refer to GES No. 0 industrial

### Risk management measures

Technical conditions and measures at process level (source) to prevent release:

Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan.

Operational conditions and risk management measures:

Locate bulk storage outdoors.

Conditions and measures related to personal protection, hygiene and health evaluation:

Use suitable eye protection.

If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to EN374 and provide employee skin care programmes.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 29 of 121

### **Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES**

'ECT Acetone': The Excel-tool enables the performance of scaling calculation for specific local environmental conditions. It can be downloaded from the web page of the Phenol & Derivatives REACH-consortium:  
<http://www.reachcentrum.eu/EN/consortium-management/consortia-under-reach/phenol-derivatives-reach-consortium.aspx>

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 30 of 121

### Exposure Scenario 3: Uses in coatings

#### List of use descriptors

Sector of uses [SU]: SU3: Industrial uses

#### Application

Activities and processes: Covers the use in coatings (paints, inks, adhesives, etc), including exposures during use (including materials receipt, storage, preparation and transfer from bulk and semi-bulk, application by spray, roller, spreader, dip, flow, fluidised bed on production lines and film formation).

Remark: Process categories [PROC]  
PROC5, PROC8a, PROC8b, PROC10, PROC13  
Process Categories (additionally):  
PROC1, PROC2, PROC3, PROC4, PROC7, PROC8b, PROC9, PROC15, PROC19  
Control of worker exposure:  
See section risk management measures  
Human Health, Worker exposure and risk assessment:  
Exposure assessment and method: Shown are the result of the quantitative exposure and risk assessment prepared based on the 'GES Worker Chemical Safety Assessment (CSA) Template'. This tool can be downloaded from the CEFIC website:  
<http://cefic.org/templates/shwPublications.asp?HID=750>

Examples for Environmental release categories [ERC]:  
ERC4

Environment, ECT acetone:  
Please use the 'ECT Acetone' to check your local conditions. The Excel-tool enables the performance of scaling calculation for specific local environmental conditions. It can be downloaded from the web page of the Phenol & Derivatives REACH-consortium:  
<http://www.reachcentrum.eu/EN/consortium-management/consortia-under-reach/phenol-derivatives-reach-consortium.aspx>

Guidance to check compliance with the exposure scenario: Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Contributing Scenarios:	1	General information Applies to all contributing exposure scenarios related to exposure scenario 3: Uses in coatings (environment)	Page 30
	2	General information Applies to all contributing exposure scenarios related to exposure scenario 3: Uses in coatings (worker)	Page 31

Contributing exposure scenario 1

#### General information

**Applies to all contributing exposure scenarios related to exposure scenario 3: Uses in coatings (environment)**

#### List of use descriptors

Environmental release categories [ERC]:  
ERC4: Use of non-reactive processing aid at industrial site (no inclusion into or onto article)

#### Operational conditions

Product characteristics: Substance is a unique structure, ketone, readily biodegradable

Amounts used:

Annual site tonnage Please use the Excel-Tool 'ECT Acetone' to calculate your maximum tonnage/year.

Duration and frequency of use:  
360 d/y

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 31 of 121

Other relevant operational conditions:

Indoor/Outdoor use

### Exposure prediction

Exposure estimation and reference to its source:

Common practices vary across sites thus conservative process release estimates used.  
Please use the 'ECT Acetone' to check your local conditions.

Risk characterisation ratio (RCR):

ECT Acetone

### Risk management measures

Technical conditions and measures at process level (source) to prevent release:

Common practices vary across sites thus conservative process release estimates used.  
Typical technical measures are closed systems or scrubbers or charcoal adsorbers.  
Treat air emission to provide a typical removal efficiency of (%): 90 %

### Disposal considerations

Conditions and measures related to sewage treatment plant:

Please use the Excel-Tool 'ECT Acetone' to check your local conditions.

Conditions and measures related to external treatment of waste for disposal:

External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste:

External treatment and disposal of waste should comply with applicable local and/or national regulations.

Contributing exposure scenario 2

### General information

**Applies to all contributing exposure scenarios related to exposure scenario 3: Uses in coatings (worker)**

### List of use descriptors

Process categories [PROC]:

PROC5: Mixing or blending in batch processes  
PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities  
PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities  
PROC10: Roller application or brushing  
PROC13: Treatment of articles by dipping and pouring  
PROC1: Use in closed process, no likelihood of exposure  
PROC2: Use in closed, continuous process with occasional controlled exposure  
PROC3: Use in closed batch process (synthesis or formulation)  
PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises  
PROC7: Industrial spraying  
PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities  
PROC9: Transfer of substance or mixture into small containers (dedicated filling line, including weighing)  
PROC15: Use as laboratory reagent  
PROC19: Hand-mixing with intimate contact and only PPE available

### Operational conditions

Duration and frequency of use:

Covers daily exposures up to 8h

### Exposure prediction

Exposure estimation and reference to its source:

refer to GES No. 0 industrial

Risk characterisation ratio (RCR):

refer to GES No. 0 industrial

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 32 of 121

### Risk management measures

Technical conditions and measures at process level (source) to prevent release:

Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan.

Operational conditions and risk management measures:

Locate bulk storage outdoors.

Conditions and measures related to personal protection, hygiene and health evaluation:

Use suitable eye protection.

If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to EN374 and provide employee skin care programmes.

### Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

'ECT Acetone': The Excel-tool enables the performance of scaling calculation for specific local environmental conditions. It can be downloaded from the web page of the Phenol & Derivatives REACH-consortium:

<http://www.reachcentrum.eu/EN/consortium-management/consortia-under-reach/phenol-derivatives-reach-consortium.aspx>



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 33 of 121

### Exposure Scenario 4: Use in binders and release agents

#### List of use descriptors

Sector of uses [SU]: SU3: Industrial uses

#### Application

Activities and processes: Covers the use as binders and release agents including material transfers, mixing, application (including spraying and brushing), mould forming and casting and handling of waste

Remark: Process categories [PROC]  
PROC1, PROC2, PROC3, PROC4, PROC5, PROC6, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC13  
Control of worker exposure:  
See section risk management measures  
Human Health, Worker exposure and risk assessment:  
Exposure assessment and method: Shown are the result of the quantitative exposure and risk assessment prepared based on the 'GES Worker Chemical Safety Assessment (CSA) Template'. This tool can be downloaded from the CEFIC website:  
<http://cefic.org/templates/shwPublications.asp?HID=750>

Examples for Environmental release categories [ERC]:  
ERC5

Environment, ECT acetone:  
Please use the 'ECT Acetone' to check your local conditions. The Excel-tool enables the performance of scaling calculation for specific local environmental conditions. It can be downloaded from the web page of the Phenol & Derivatives REACH-consortium:  
<http://www.reachcentrum.eu/EN/consortium-management/consortia-under-reach/phenol-derivatives-reach-consortium.aspx>

Guidance to check compliance with the exposure scenario: Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Contributing Scenarios:	1	General information Applies to all contributing exposure scenarios related to exposure scenario 4: Use in binders and release agents (environment)	Page 33
	2	General information Applies to all contributing exposure scenarios related to exposure scenario 4: Use in binders and release agents (worker)	Page 34

Contributing exposure scenario 1

#### General information

**Applies to all contributing exposure scenarios related to exposure scenario 4: Use in binders and release agents (environment)**

#### List of use descriptors

Environmental release categories [ERC]:  
ERC5: Use at industrial site leading to inclusion into/onto article

#### Operational conditions

Product characteristics: Substance is a unique structure, ketone, readily biodegradable  
Amounts used:  
Annual site tonnage Please use the Excel-Tool 'ECT Acetone' to calculate your maximum tonnage/year.

Duration and frequency of use:  
360 d/y

Other relevant operational conditions:  
Indoor/Outdoor use

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 34 of 121

### Exposure prediction

Exposure estimation and reference to its source:

Common practices vary across sites thus conservative process release estimates used.  
Please use the 'ECT Acetone' to check your local conditions.

Risk characterisation ratio (RCR):

ECT Acetone

### Risk management measures

Technical conditions and measures at process level (source) to prevent release:

Common practices vary across sites thus conservative process release estimates used.  
Typical technical measures are closed systems or scrubbers or charcoal adsorbers.  
Treat air emission to provide a typical removal efficiency of (%): 90 %

### Disposal considerations

Conditions and measures related to sewage treatment plant:

Please use the Excel-Tool 'ECT Acetone' to check your local conditions.

Conditions and measures related to external treatment of waste for disposal:

External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste:

External treatment and disposal of waste should comply with applicable local and/or national regulations.

Contributing exposure scenario 2

### General information

**Applies to all contributing exposure scenarios related to exposure scenario 4: Use in binders and release agents (worker)**

### List of use descriptors

Process categories [PROC]:

- PROC1: Use in closed process, no likelihood of exposure
- PROC2: Use in closed, continuous process with occasional controlled exposure
- PROC3: Use in closed batch process (synthesis or formulation)
- PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises
- PROC5: Mixing or blending in batch processes
- PROC6: Calendering operations
- PROC7: Industrial spraying
- PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities
- PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities
- PROC9: Transfer of substance or mixture into small containers (dedicated filling line, including weighing)
- PROC10: Roller application or brushing
- PROC13: Treatment of articles by dipping and pouring

### Operational conditions

Product characteristics: liquid, vapour pressure > 10 kPa

Concentration of the substance in a mixture:

Covers percentage substance in the product up to 100 % (unless stated differently.)

Duration and frequency of use:

Covers daily exposures up to 8h

Other relevant operational conditions:

Assumes a good basic standard of occupational hygiene is implemented.

### Exposure prediction

Exposure estimation and reference to its source:

refer to GES No. 0 industrial

Risk characterisation ratio (RCR):

refer to GES No. 0 industrial

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 35 of 121

### Risk management measures

Technical conditions and measures at process level (source) to prevent release:

Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan.

Operational conditions and risk management measures:

Locate bulk storage outdoors.

Conditions and measures related to personal protection, hygiene and health evaluation:

Use suitable eye protection.

If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to EN374 and provide employee skin care programmes.

### Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

'ECT Acetone': The Excel-tool enables the performance of scaling calculation for specific local environmental conditions. It can be downloaded from the web page of the Phenol & Derivatives REACH-consortium:

<http://www.reachcentrum.eu/EN/consortium-management/consortia-under-reach/phenol-derivatives-reach-consortium.aspx>

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 36 of 121

### Exposure Scenario 5: Rubber production and processing

#### List of use descriptors

Sector of uses [SU]: SU3: Industrial uses

#### Application

Activities and processes: Manufacture of tyres and general rubber articles, including processing of raw (uncured) rubber, handling and mixing of rubber additives, vulcanising, cooling and finishing.

Remark: Process categories [PROC]  
PROC1, PROC2, PROC3, PROC4, PROC5, PROC6, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC14

Control of worker exposure:  
See section risk management measures

Human Health, Worker exposure and risk assessment:  
Exposure assessment and method: Shown are the result of the quantitative exposure and risk assessment prepared based on the 'GES Worker Chemical Safety Assessment (CSA) Template'. This tool can be downloaded from the CEFIC website:  
<http://cefic.org/templates/shwPublications.asp?HID=750>

Examples for Environmental release categories [ERC]:  
ERC6d

Environment, ECT acetone:  
Please use the 'ECT Acetone' to check your local conditions. The Excel-tool enables the performance of scaling calculation for specific local environmental conditions. It can be downloaded from the web page of the Phenol & Derivatives REACH-consortium:  
<http://www.reachcentrum.eu/EN/consortium-management/consortia-under-reach/phenol-derivatives-reach-consortium.aspx>

Guidance to check compliance with the exposure scenario: Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Contributing Scenarios:	1	General information Applies to all contributing exposure scenarios related to exposure scenario 5: Rubber production and processing (environment)	Page 36
	2	General information Applies to all contributing exposure scenarios related to exposure scenario 5: Rubber production and processing (worker)	Page 37

Contributing exposure scenario 1

#### General information

**Applies to all contributing exposure scenarios related to exposure scenario 5: Rubber production and processing (environment)**

#### List of use descriptors

Environmental release categories [ERC]:  
ERC6d: Use of reactive process regulators in polymerisation processes at industrial site (inclusion or not into/onto article)

#### Operational conditions

Product characteristics: Substance is a unique structure, ketone, readily biodegradable  
Amounts used:  
Annual site tonnage Please use the Excel-Tool 'ECT Acetone' to calculate your maximum tonnage/year.

Duration and frequency of use:  
360 d/y

Other relevant operational conditions:  
Indoor/Outdoor use

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 37 of 121

### Exposure prediction

Exposure estimation and reference to its source:

Common practices vary across sites thus conservative process release estimates used.  
Please use the 'ECT Acetone' to check your local conditions.

Risk characterisation ratio (RCR):

ECT Acetone

### Risk management measures

Technical conditions and measures at process level (source) to prevent release:

Common practices vary across sites thus conservative process release estimates used.  
Typical technical measures are closed systems or scrubbers or charcoal adsorbers.  
Treat air emission to provide a typical removal efficiency of (%): 90 %

### Disposal considerations

Conditions and measures related to sewage treatment plant:

Please use the Excel-Tool 'ECT Acetone' to check your local conditions.

Conditions and measures related to external treatment of waste for disposal:

External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste:

External treatment and disposal of waste should comply with applicable local and/or national regulations.

Contributing exposure scenario 2

### General information

**Applies to all contributing exposure scenarios related to exposure scenario 5: Rubber production and processing (worker)**

### List of use descriptors

Process categories [PROC]:

- PROC1: Use in closed process, no likelihood of exposure
- PROC2: Use in closed, continuous process with occasional controlled exposure
- PROC3: Use in closed batch process (synthesis or formulation)
- PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises
- PROC5: Mixing or blending in batch processes
- PROC6: Calendering operations
- PROC7: Industrial spraying
- PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities
- PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities
- PROC9: Transfer of substance or mixture into small containers (dedicated filling line, including weighing)
- PROC10: Roller application or brushing
- PROC13: Treatment of articles by dipping and pouring
- PROC14: Production of preparations or articles by tableting, compression, extrusion, pelletisation

### Operational conditions

Product characteristics: liquid, vapour pressure > 10 kPa

Concentration of the substance in a mixture:

Covers percentage substance in the product up to 100 % (unless stated differently.)

Duration and frequency of use:

Covers daily exposures up to 8h

Other relevant operational conditions:

Assumes a good basic standard of occupational hygiene is implemented.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 38 of 121

### Exposure prediction

Exposure estimation and reference to its source:

refer to GES No. 0 industrial

Risk characterisation ratio (RCR):

refer to GES No. 0 industrial

### Risk management measures

Technical conditions and measures at process level (source) to prevent release:

Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan.

Operational conditions and risk management measures:

Locate bulk storage outdoors.

Conditions and measures related to personal protection, hygiene and health evaluation:

Use suitable eye protection.

If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to EN374 and provide employee skin care programmes.

### Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

'ECT Acetone': The Excel-tool enables the performance of scaling calculation for specific local environmental conditions. It can be downloaded from the web page of the Phenol & Derivatives REACH-consortium:

<http://www.reachcentrum.eu/EN/consortium-management/consortia-under-reach/phenol-derivatives-reach-consortium.aspx>

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 39 of 121

### Exposure Scenario 6: Polymer manufacturing

#### List of use descriptors

Sector of uses [SU]: SU3: Industrial uses

#### Application

Activities and processes: Manufacturing of formulated polymers including material transfers, additives handling (e.g. pigments, stabilisers, fillers, plasticisers, etc.), moulding, curing and forming activities, material re-works, storage and associated maintenance

Remark: Process categories [PROC]  
PROC1, PROC2, PROC3, PROC4, PROC5, PROC6, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC14, PROC15  
Control of worker exposure:  
See section risk management measures  
Human Health, Worker exposure and risk assessment:  
Exposure assessment and method: Shown are the result of the quantitative exposure and risk assessment prepared based on the 'GES Worker Chemical Safety Assessment (CSA) Template'. This tool can be downloaded from the CEFIC website:  
<http://cefic.org/templates/shwPublications.asp?HID=750>

Examples for Environmental release categories [ERC]:  
ERC6d

Environment, ECT acetone:  
Please use the 'ECT Acetone' to check your local conditions. The Excel-tool enables the performance of scaling calculation for specific local environmental conditions. It can be downloaded from the web page of the Phenol & Derivatives REACH-consortium:  
<http://www.reachcentrum.eu/EN/consortium-management/consortia-under-reach/phenol-derivatives-reach-consortium.aspx>

Guidance to check compliance with the exposure scenario: Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Contributing Scenarios:	1	General information Applies to all contributing exposure scenarios related to exposure scenario 6: Polymer manufacturing (environment)	Page 39
	2	General information Applies to all contributing exposure scenarios related to exposure scenario 6: Polymer manufacturing (worker)	Page 40

Contributing exposure scenario 1

#### General information

**Applies to all contributing exposure scenarios related to exposure scenario 6: Polymer manufacturing (environment)**

#### List of use descriptors

Environmental release categories [ERC]:  
ERC6d: Use of reactive process regulators in polymerisation processes at industrial site (inclusion or not into/onto article)

#### Operational conditions

Product characteristics: Substance is a unique structure, ketone, readily biodegradable  
Amounts used:  
Annual site tonnage Please use the Excel-Tool 'ECT Acetone' to calculate your maximum tonnage/year.

Duration and frequency of use:  
360 d/y

Other relevant operational conditions:  
Indoor/Outdoor use

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 40 of 121

### Exposure prediction

Exposure estimation and reference to its source:

Common practices vary across sites thus conservative process release estimates used.  
Please use the 'ECT Acetone' to check your local conditions.

Risk characterisation ratio (RCR):

ECT Acetone

### Risk management measures

Technical conditions and measures at process level (source) to prevent release:

Common practices vary across sites thus conservative process release estimates used.  
Typical technical measures are closed systems or scrubbers or charcoal adsorbers.  
Treat air emission to provide a typical removal efficiency of (%): 90 %

### Disposal considerations

Conditions and measures related to sewage treatment plant:

Please use the Excel-Tool 'ECT Acetone' to check your local conditions.

Conditions and measures related to external treatment of waste for disposal:

External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste:

External treatment and disposal of waste should comply with applicable local and/or national regulations.

Contributing exposure scenario 2

### General information

**Applies to all contributing exposure scenarios related to exposure scenario 6: Polymer manufacturing (worker)**

### List of use descriptors

Process categories [PROC]:

- PROC1: Use in closed process, no likelihood of exposure
- PROC2: Use in closed, continuous process with occasional controlled exposure
- PROC3: Use in closed batch process (synthesis or formulation)
- PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises
- PROC5: Mixing or blending in batch processes
- PROC6: Calendaring operations
- PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities
- PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities
- PROC9: Transfer of substance or mixture into small containers (dedicated filling line, including weighing)
- PROC10: Roller application or brushing
- PROC13: Treatment of articles by dipping and pouring
- PROC14: Production of preparations or articles by tableting, compression, extrusion, pelletisation
- PROC15: Use as laboratory reagent

### Operational conditions

Product characteristics: liquid, vapour pressure > 10 kPa

Concentration of the substance in a mixture:

Covers percentage substance in the product up to 100 % (unless stated differently.)

Duration and frequency of use:

Covers daily exposures up to 8h

Other relevant operational conditions:

Assumes a good basic standard of occupational hygiene is implemented.



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

**INEOS Phenol**

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 41 of 121

### Exposure prediction

Exposure estimation and reference to its source:

refer to GES No. 0 industrial

Risk characterisation ratio (RCR):

refer to GES No. 0 industrial

### Risk management measures

Technical conditions and measures at process level (source) to prevent release:

Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan.

Operational conditions and risk management measures:

Locate bulk storage outdoors.

Conditions and measures related to personal protection, hygiene and health evaluation:

Use suitable eye protection.

If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to EN374 and provide employee skin care programmes.

### Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

'ECT Acetone': The Excel-tool enables the performance of scaling calculation for specific local environmental conditions. It can be downloaded from the web page of the Phenol & Derivatives REACH-consortium:

<http://www.reachcentrum.eu/EN/consortium-management/consortia-under-reach/phenol-derivatives-reach-consortium.aspx>

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 42 of 121

### Exposure Scenario 7: Polymer processing

#### List of use descriptors

Sector of uses [SU]: SU3: Industrial uses

#### Application

Activities and processes: Processing of formulated polymers including incidental exposures during material transfers, additives handling (e.g. pigments, stabilisers, fillers, plasticisers, etc.), moulding, curing and forming activities, material re-works, storage and associated maintenance

Remark: Process categories [PROC]  
PROC1, PROC2, PROC3, PROC4, PROC5, PROC6, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC14, PROC15  
Control of worker exposure:  
See section risk management measures  
Human Health, Worker exposure and risk assessment:  
Exposure assessment and method: Shown are the result of the quantitative exposure and risk assessment prepared based on the 'GES Worker Chemical Safety Assessment (CSA) Template'. This tool can be downloaded from the CEFIC website:  
<http://cefic.org/templates/shwPublications.asp?HID=750>

Examples for Environmental release categories [ERC]:  
ERC6d

Environment, ECT acetone:

Please use the 'ECT Acetone' to check your local conditions. The Excel-tool enables the performance of scaling calculation for specific local environmental conditions. It can be downloaded from the web page of the Phenol & Derivatives REACH-consortium:  
<http://www.reachcentrum.eu/EN/consortium-management/consortia-under-reach/phenol-derivatives-reach-consortium.aspx>

Guidance to check compliance with the exposure scenario: Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Contributing Scenarios:	1	General information Applies to all contributing exposure scenarios related to exposure scenario 7: Polymer processing (environment)	Page 42
	2	General information Applies to all contributing exposure scenarios related to exposure scenario 7: Polymer processing (worker)	Page 43

Contributing exposure scenario 1

#### General information

**Applies to all contributing exposure scenarios related to exposure scenario 7: Polymer processing (environment)**

#### List of use descriptors

Environmental release categories [ERC]:

ERC6d: Use of reactive process regulators in polymerisation processes at industrial site (inclusion or not into/onto article)

#### Operational conditions

Product characteristics: Substance is a unique structure, ketone, readily biodegradable  
Amounts used:  
Annual site tonnage Please use the Excel-Tool 'ECT Acetone' to calculate your maximum tonnage/year.

Duration and frequency of use:  
360 d/y

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 43 of 121

Other relevant operational conditions:

Indoor/Outdoor use

### Exposure prediction

Exposure estimation and reference to its source:

Common practices vary across sites thus conservative process release estimates used.  
Please use the 'ECT Acetone' to check your local conditions.

Risk characterisation ratio (RCR):

ECT Acetone

### Risk management measures

Technical conditions and measures at process level (source) to prevent release:

Common practices vary across sites thus conservative process release estimates used.  
Typical technical measures are closed systems or scrubbers or charcoal adsorbers.  
Treat air emission to provide a typical removal efficiency of (%): 90 %

### Disposal considerations

Conditions and measures related to sewage treatment plant:

Please use the Excel-Tool 'ECT Acetone' to check your local conditions.

Conditions and measures related to external treatment of waste for disposal:

External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste:

External treatment and disposal of waste should comply with applicable local and/or national regulations.

Contributing exposure scenario 2

### General information

**Applies to all contributing exposure scenarios related to exposure scenario 7: Polymer processing (worker)**

### List of use descriptors

Process categories [PROC]:

- PROC1: Use in closed process, no likelihood of exposure
- PROC2: Use in closed, continuous process with occasional controlled exposure
- PROC3: Use in closed batch process (synthesis or formulation)
- PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises
- PROC5: Mixing or blending in batch processes
- PROC6: Calendaring operations
- PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities
- PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities
- PROC9: Transfer of substance or mixture into small containers (dedicated filling line, including weighing)
- PROC10: Roller application or brushing
- PROC13: Treatment of articles by dipping and pouring
- PROC14: Production of preparations or articles by tableting, compression, extrusion, pelletisation
- PROC15: Use as laboratory reagent

### Operational conditions

Product characteristics: liquid, vapour pressure > 10 kPa

Concentration of the substance in a mixture:

Covers percentage substance in the product up to 100 % (unless stated differently.)

Duration and frequency of use:

Covers daily exposures up to 8h

Other relevant operational conditions:

Assumes a good basic standard of occupational hygiene is implemented.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 44 of 121

### Exposure prediction

Exposure estimation and reference to its source:

refer to GES No. 0 industrial

Risk characterisation ratio (RCR):

refer to GES No. 0 industrial

### Risk management measures

Technical conditions and measures at process level (source) to prevent release:

Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan.

Operational conditions and risk management measures:

Locate bulk storage outdoors.

Conditions and measures related to personal protection, hygiene and health evaluation:

Use suitable eye protection.

If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to EN374 and provide employee skin care programmes.

### Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

'ECT Acetone': The Excel-tool enables the performance of scaling calculation for specific local environmental conditions. It can be downloaded from the web page of the Phenol & Derivatives REACH-consortium:

<http://www.reachcentrum.eu/EN/consortium-management/consortia-under-reach/phenol-derivatives-reach-consortium.aspx>

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 45 of 121

### Exposure Scenario 8: Use in cleaning agents

#### List of use descriptors

Sector of uses [SU]: SU3: Industrial uses

#### Application

Activities and processes: Covers the use as a component of cleaning products including transfer from storage, pouring/unloading from drums or containers exposures during mixing/diluting in the preparatory phase and cleaning activities (including spraying, brushing, dipping, wiping, automated and by hand) related equipment cleaning and maintenance

Remark: Process categories [PROC]  
PROC1, PROC2, PROC3, PROC4, PROC5, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC19  
Control of worker exposure:  
See section risk management measures  
Human Health, Worker exposure and risk assessment:  
Exposure assessment and method: Shown are the result of the quantitative exposure and risk assessment prepared based on the 'GES Worker Chemical Safety Assessment (CSA) Template'. This tool can be downloaded from the CEFIC website:  
<http://cefic.org/templates/shwPublications.asp?HID=750>

Examples for Environmental release categories [ERC]:  
ERC4d

Environment, ECT acetone:

Please use the 'ECT Acetone' to check your local conditions. The Excel-tool enables the performance of scaling calculation for specific local environmental conditions. It can be downloaded from the web page of the Phenol & Derivatives REACH-consortium:  
<http://www.reachcentrum.eu/EN/consortium-management/consortia-under-reach/phenol-derivatives-reach-consortium.aspx>

Guidance to check compliance with the exposure scenario: Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Contributing Scenarios:	1	General information Applies to all contributing exposure scenarios related to exposure scenario 9: Use in cleaning agents (environment)	Page 45
	2	General information Applies to all contributing exposure scenarios related to exposure scenario 9: Use in cleaning agents (worker)	Page 46

Contributing exposure scenario 1

#### General information

**Applies to all contributing exposure scenarios related to exposure scenario 9: Use in cleaning agents (environment)**

#### List of use descriptors

Environmental release categories [ERC]:  
ERC4: Use of non-reactive processing aid at industrial site (no inclusion into or onto article)

#### Operational conditions

Product characteristics: Substance is a unique structure, ketone, readily biodegradable  
Amounts used:  
Annual site tonnage Please use the Excel-Tool 'ECT Acetone' to calculate your maximum tonnage/year.

Duration and frequency of use:  
360 d/y

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 46 of 121

Other relevant operational conditions:

Indoor/Outdoor use

### Exposure prediction

Exposure estimation and reference to its source:

Common practices vary across sites thus conservative process release estimates used.  
Please use the 'ECT Acetone' to check your local conditions.

Risk characterisation ratio (RCR):

ECT Acetone

### Risk management measures

Technical conditions and measures at process level (source) to prevent release:

Common practices vary across sites thus conservative process release estimates used.  
Typical technical measures are closed systems or scrubbers or charcoal adsorbers.  
Treat air emission to provide a typical removal efficiency of (%): 90 %

### Disposal considerations

Conditions and measures related to sewage treatment plant:

Please use the Excel-Tool 'ECT Acetone' to check your local conditions.

Conditions and measures related to external treatment of waste for disposal:

External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste:

External treatment and disposal of waste should comply with applicable local and/or national regulations.

Contributing exposure scenario 2

### General information

**Applies to all contributing exposure scenarios related to exposure scenario 9: Use in cleaning agents (worker)**

### List of use descriptors

Process categories [PROC]:

- PROC1: Use in closed process, no likelihood of exposure
- PROC2: Use in closed, continuous process with occasional controlled exposure
- PROC3: Use in closed batch process (synthesis or formulation)
- PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises
- PROC5: Mixing or blending in batch processes
- PROC7: Industrial spraying
- PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities
- PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities
- PROC9: Transfer of substance or mixture into small containers (dedicated filling line, including weighing)
- PROC10: Roller application or brushing
- PROC13: Treatment of articles by dipping and pouring
- PROC19: Hand-mixing with intimate contact and only PPE available

### Operational conditions

Product characteristics: liquid, vapour pressure > 10 kPa

Concentration of the substance in a mixture:

Covers percentage substance in the product up to 100 % (unless stated differently.)

Duration and frequency of use:

Covers daily exposures up to 8h

Other relevant operational conditions:

Assumes a good basic standard of occupational hygiene is implemented.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 47 of 121

### Exposure prediction

Exposure estimation and reference to its source:

refer to GES No. 0 industrial

Risk characterisation ratio (RCR):

refer to GES No. 0 industrial

### Risk management measures

Technical conditions and measures at process level (source) to prevent release:

Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan.

Operational conditions and risk management measures:

Locate bulk storage outdoors.

Conditions and measures related to personal protection, hygiene and health evaluation:

Use suitable eye protection.

If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to EN374 and provide employee skin care programmes.

### Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

'ECT Acetone': The Excel-tool enables the performance of scaling calculation for specific local environmental conditions. It can be downloaded from the web page of the Phenol & Derivatives REACH-consortium:

<http://www.reachcentrum.eu/EN/consortium-management/consortia-under-reach/phenol-derivatives-reach-consortium.aspx>

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 48 of 121

### Exposure Scenario 9: Use in oil and gas field drilling and production operations

#### List of use descriptors

Sector of uses [SU]: SU3: Industrial uses

#### Application

Activities and processes: Covers the use as a component of cleaning products including transfer from storage, pouring/unloading from drums or containers

Remark: Process categories [PROC]  
PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b

Control of worker exposure:

See section risk management measures

Human Health, Worker exposure and risk assessment:

Exposure assessment and method: Shown are the result of the quantitative exposure and risk assessment prepared based on the 'GES Worker Chemical Safety Assessment (CSA) Template'. This tool can be downloaded from the CEFIC website:

<http://cefic.org/templates/shwPublications.asp?HID=750>

Examples for Environmental release categories [ERC]:

ERC4

Environment, ECT acetone:

Please use the 'ECT Acetone' to check your local conditions. The Excel-tool enables the performance of scaling calculation for specific local environmental conditions. It can be downloaded from the web page of the Phenol & Derivatives REACH-consortium:

<http://www.reachcentrum.eu/EN/consortium-management/consortia-under-reach/phenol-derivatives-reach-consortium.aspx>

Guidance to check compliance with the exposure scenario: Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Contributing Scenarios:	1	General information Applies to all contributing exposure scenarios related to exposure scenario 10: Use in oil and gas field drilling and production operations (environment)	Page 48
	2	General information Applies to all contributing exposure scenarios related to exposure scenario 10: Use in oil and gas field drilling and production operations (worker)	Page 49

Contributing exposure scenario 1

#### General information

**Applies to all contributing exposure scenarios related to exposure scenario 10: Use in oil and gas field drilling and production operations (environment)**

#### List of use descriptors

Environmental release categories [ERC]:

ERC4: Use of non-reactive processing aid at industrial site (no inclusion into or onto article)

#### Operational conditions

Product characteristics: Substance is a unique structure, ketone, readily biodegradable

Amounts used:

Annual site tonnage Please use the Excel-Tool 'ECT Acetone' to calculate your maximum tonnage/year.

Duration and frequency of use:

360 d/y



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 49 of 121

Other relevant operational conditions:

Indoor/Outdoor use

### Exposure prediction

Exposure estimation and reference to its source:

Common practices vary across sites thus conservative process release estimates used.  
Please use the 'ECT Acetone' to check your local conditions.

Risk characterisation ratio (RCR):

ECT Acetone

### Risk management measures

Technical conditions and measures at process level (source) to prevent release:

Common practices vary across sites thus conservative process release estimates used.  
Typical technical measures are closed systems or scrubbers or charcoal adsorbers.  
Treat air emission to provide a typical removal efficiency of (%): 90 %

### Disposal considerations

Conditions and measures related to sewage treatment plant:

Please use the Excel-Tool 'ECT Acetone' to check your local conditions.

Conditions and measures related to external treatment of waste for disposal:

External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste:

External treatment and disposal of waste should comply with applicable local and/or national regulations.

Contributing exposure scenario 2

### General information

**Applies to all contributing exposure scenarios related to exposure scenario 10: Use in oil and gas field drilling and production operations (worker)**

### List of use descriptors

Process categories [PROC]:

PROC1: Use in closed process, no likelihood of exposure  
PROC2: Use in closed, continuous process with occasional controlled exposure  
PROC3: Use in closed batch process (synthesis or formulation)  
PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises  
PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities  
PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

### Operational conditions

Product characteristics: liquid, vapour pressure > 10 kPa

Concentration of the substance in a mixture:

Covers percentage substance in the product up to 100 % (unless stated differently.)

Duration and frequency of use:

Covers daily exposures up to 8h

### Exposure prediction

Exposure estimation and reference to its source:

refer to GES No. 0 industrial

Risk characterisation ratio (RCR):

refer to GES No. 0 industrial

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

**INEOS Phenol**

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 50 of 121

### Risk management measures

Technical conditions and measures at process level (source) to prevent release:

Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan.

Operational conditions and risk management measures:

Locate bulk storage outdoors.

Conditions and measures related to personal protection, hygiene and health evaluation:

Use suitable eye protection.

If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to EN374 and provide employee skin care programmes.

### Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

'ECT Acetone': The Excel-tool enables the performance of scaling calculation for specific local environmental conditions. It can be downloaded from the web page of the Phenol & Derivatives REACH-consortium:

<http://www.reachcentrum.eu/EN/consortium-management/consortia-under-reach/phenol-derivatives-reach-consortium.aspx>

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 51 of 121

### Exposure Scenario 10: Blowing agents

#### List of use descriptors

Sector of uses [SU]: SU3: Industrial uses

#### Application

Activities and processes: Use as a blowing agent for rigid and flexible foams, including material transfers, mixing and injection, curing, cutting, storage and packing.

Remark: Process categories [PROC]  
PROC1, PROC2, PROC3, PROC8b, PROC9, PROC12

Control of worker exposure:  
See section risk management measures

Human Health, Worker exposure and risk assessment:  
Exposure assessment and method: Shown are the result of the quantitative exposure and risk assessment prepared based on the 'GES Worker Chemical Safety Assessment (CSA) Template'. This tool can be downloaded from the CEFIC website:  
<http://cefic.org/templates/shwPublications.asp?HID=750>

Examples for Environmental release categories [ERC]:  
ERC4 (ERC10a)

Environment, ECT acetone:  
Please use the 'ECT Acetone' to check your local conditions. The Excel-tool enables the performance of scaling calculation for specific local environmental conditions. It can be downloaded from the web page of the Phenol & Derivatives REACH-consortium:  
<http://www.reachcentrum.eu/EN/consortium-management/consortia-under-reach/phenol-derivatives-reach-consortium.aspx>

Guidance to check compliance with the exposure scenario: Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Contributing Scenarios:	1	General information Applies to all contributing exposure scenarios related to exposure scenario 11: Blowing agents (environment)	Page 51
	2	General information Applies to all contributing exposure scenarios related to exposure scenario 11: Blowing agents (worker)	Page 52

Contributing exposure scenario 1

#### General information

**Applies to all contributing exposure scenarios related to exposure scenario 11: Blowing agents (environment)**

#### List of use descriptors

Environmental release categories [ERC]:  
ERC4: Use of non-reactive processing aid at industrial site (no inclusion into or onto article)  
ERC10a: Wide dispersive outdoor use of long-life articles and materials with low release

#### Operational conditions

Product characteristics: Substance is a unique structure, ketone, readily biodegradable  
Amounts used:  
Annual site tonnage Please use the Excel-Tool 'ECT Acetone' to calculate your maximum tonnage/year.

Duration and frequency of use:  
360 d/y

Other relevant operational conditions:  
Indoor/Outdoor use

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 52 of 121

### Exposure prediction

Exposure estimation and reference to its source:

Common practices vary across sites thus conservative process release estimates used.  
Please use the 'ECT Acetone' to check your local conditions.

Risk characterisation ratio (RCR):

ECT Acetone

### Risk management measures

Technical conditions and measures at process level (source) to prevent release:

Common practices vary across sites thus conservative process release estimates used.  
Typical technical measures are closed systems or scrubbers or charcoal adsorbers.  
Treat air emission to provide a typical removal efficiency of (%): 90 %

### Disposal considerations

Conditions and measures related to sewage treatment plant:

Please use the Excel-Tool 'ECT Acetone' to check your local conditions.

Conditions and measures related to external treatment of waste for disposal:

External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste:

External treatment and disposal of waste should comply with applicable local and/or national regulations.

Contributing exposure scenario 2

### General information

**Applies to all contributing exposure scenarios related to exposure scenario 11: Blowing agents (worker)**

### List of use descriptors

Process categories [PROC]:

- PROC1: Use in closed process, no likelihood of exposure
- PROC2: Use in closed, continuous process with occasional controlled exposure
- PROC3: Use in closed batch process (synthesis or formulation)
- PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities
- PROC9: Transfer of substance or mixture into small containers (dedicated filling line, including weighing)
- PROC12: Use of blowing agents in manufacture of foam

### Operational conditions

Product characteristics: liquid, vapour pressure > 10 kPa

Concentration of the substance in a mixture:

Covers percentage substance in the product up to 100 % (unless stated differently.)

Duration and frequency of use:

Covers daily exposures up to 8h

Other relevant operational conditions:

Assumes a good basic standard of occupational hygiene is implemented.

### Exposure prediction

Exposure estimation and reference to its source:

refer to GES No. 0 industrial

Risk characterisation ratio (RCR):

refer to GES No. 0 industrial

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 53 of 121

### Risk management measures

Technical conditions and measures at process level (source) to prevent release:

Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan.

Operational conditions and risk management measures:

Locate bulk storage outdoors.

Conditions and measures related to personal protection, hygiene and health evaluation:

Use suitable eye protection.

If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to EN374 and provide employee skin care programmes.

### Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

'ECT Acetone': The Excel-tool enables the performance of scaling calculation for specific local environmental conditions. It can be downloaded from the web page of the Phenol & Derivatives REACH-consortium:

<http://www.reachcentrum.eu/EN/consortium-management/consortia-under-reach/phenol-derivatives-reach-consortium.aspx>

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 54 of 121

### Exposure Scenario 11: Mining chemicals

#### List of use descriptors

Sector of uses [SU]: SU3: Industrial uses

#### Application

Activities and processes: Covers the use of the substance in extraction processes at mining operations, including material transfers, winning and separation activities, and substance recovery and disposal

Remark: Process categories [PROC]  
PROC1, PROC2, PROC3, PROC4, PROC5, PROC8b, PROC9

Control of worker exposure:  
See section risk management measures

Human Health, Worker exposure and risk assessment:  
Exposure assessment and method: Shown are the result of the quantitative exposure and risk assessment prepared based on the 'GES Worker Chemical Safety Assessment (CSA) Template'. This tool can be downloaded from the CEFIC website:  
<http://cefic.org/templates/shwPublications.asp?HID=750>

Examples for Environmental release categories [ERC]:  
ERC8d

Environment, ECT acetone:  
Please use the 'ECT Acetone' to check your local conditions. The Excel-tool enables the performance of scaling calculation for specific local environmental conditions. It can be downloaded from the web page of the Phenol & Derivatives REACH-consortium:  
<http://www.reachcentrum.eu/EN/consortium-management/consortia-under-reach/phenol-derivatives-reach-consortium.aspx>

Guidance to check compliance with the exposure scenario: Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Contributing Scenarios:	1	General information Applies to all contributing exposure scenarios related to exposure scenario 12: Mining chemicals (environment)	Page 54
	2	General information Applies to all contributing exposure scenarios related to exposure scenario 12: Mining chemicals (worker)	Page 55

Contributing exposure scenario 1

#### General information

**Applies to all contributing exposure scenarios related to exposure scenario 12: Mining chemicals (environment)**

#### List of use descriptors

Environmental release categories [ERC]:  
ERC8d: wide dispersive outdoor use of processing aids in open systems

#### Operational conditions

Product characteristics: Substance is a unique structure, ketone, readily biodegradable

Amounts used:  
Annual site tonnage Please use the Excel-Tool 'ECT Acetone' to calculate your maximum tonnage/year.

Duration and frequency of use:  
360 d/y

Other relevant operational conditions:  
Indoor/Outdoor use

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 55 of 121

### Exposure prediction

Exposure estimation and reference to its source:

Common practices vary across sites thus conservative process release estimates used.  
Please use the 'ECT Acetone' to check your local conditions.

Risk characterisation ratio (RCR):

ECT Acetone

### Risk management measures

Technical conditions and measures at process level (source) to prevent release:

Common practices vary across sites thus conservative process release estimates used.  
Typical technical measures are closed systems or scrubbers or charcoal adsorbers.  
Treat air emission to provide a typical removal efficiency of (%): 90 %

### Disposal considerations

Conditions and measures related to sewage treatment plant:

Please use the Excel-Tool 'ECT Acetone' to check your local conditions.

Conditions and measures related to external treatment of waste for disposal:

External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste:

External treatment and disposal of waste should comply with applicable local and/or national regulations.

Contributing exposure scenario 2

### General information

**Applies to all contributing exposure scenarios related to exposure scenario 12: Mining chemicals (worker)**

### List of use descriptors

Process categories [PROC]:

- PROC1: Use in closed process, no likelihood of exposure
- PROC2: Use in closed, continuous process with occasional controlled exposure
- PROC3: Use in closed batch process (synthesis or formulation)
- PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises
- PROC5: Mixing or blending in batch processes
- PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities
- PROC9: Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

### Operational conditions

Product characteristics: liquid, vapour pressure > 10 kPa

Concentration of the substance in a mixture:

Covers percentage substance in the product up to 100 % (unless stated differently.)

Duration and frequency of use:

Covers daily exposures up to 8h

Other relevant operational conditions:

Assumes a good basic standard of occupational hygiene is implemented.

### Exposure prediction

Exposure estimation and reference to its source:

refer to GES No. 0 industrial

Risk characterisation ratio (RCR):

refer to GES No. 0 industrial

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

**INEOS Phenol**

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 56 of 121

### Risk management measures

Technical conditions and measures at process level (source) to prevent release:

Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan.

Operational conditions and risk management measures:

Locate bulk storage outdoors.

Conditions and measures related to personal protection, hygiene and health evaluation:

Use suitable eye protection.

If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to EN374 and provide employee skin care programmes.

### Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

'ECT Acetone': The Excel-tool enables the performance of scaling calculation for specific local environmental conditions. It can be downloaded from the web page of the Phenol & Derivatives REACH-consortium:

<http://www.reachcentrum.eu/EN/consortium-management/consortia-under-reach/phenol-derivatives-reach-consortium.aspx>



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 57 of 121

### Exposure Scenario 12: Generic exposure scenario (GES): Professional Processes relevant for Acetone containing products (ES 13 - 22)

#### List of use descriptors

Sector of uses [SU]: SU22: Professional uses

#### Application

Activities and processes: Generic exposure scenario, applies to all contributing exposure scenarios related to exposure scenario 13 - 22 (professional uses):

- ES13 - Use in laboratories
- ES14 - Uses in coatings
- ES15 - Use in binders and release agents
- ES16 - Polymer manufacturing
- ES17 - Polymer processing
- ES18 - Use in cleaning agents
- ES19 - Use in oil and gas field drilling and production operations
- ES20 - Agrochemical uses
- ES21 - De-icing and anti-icing applications
- ES22 - Explosives manufacture & use

Contributing Scenarios:	1	Use in closed process, no likelihood of exposure General exposures (closed systems) (worker)	Page 58
	2	Use in closed, continuous process with occasional controlled exposure General exposures (closed systems) (worker)	Page 59
	3	Use in closed batch process (synthesis or formulation) General exposures (closed systems) (worker)	Page 59
	4	Use in batch and other process (synthesis) where opportunity for exposure arises Process sampling (open systems) (worker)	Page 60
	5	Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact) Mixing operations (open systems) (worker)	Page 60
	6	Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact) Mixing operations (open systems) (worker)	Page 61
	7	Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact) Mixing operations (open systems) (worker)	Page 61
	8	Calendering operations Calendering (including Banburys); with local exhaust ventilation (worker)	Page 62
	9	Calendering operations Calendering (including Banburys) (worker)	Page 62
	10	Calendering operations Calendering (including Banburys) (worker)	Page 62
	11	Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities Bulk transfers (worker)	Page 63
	12	Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities Bulk transfers (worker)	Page 63
	13	Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities Bulk transfers (worker)	Page 64

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 58 of 121

Contributing Scenarios:	14	Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities Bulk transfers (worker)	Page 64
	15	Transfer of substance or preparation into small containers (dedicated filling line, including weighing) Small package filling (worker)	Page 65
	16	Roller application or brushing Equipment cleaning and maintenance (worker)	Page 65
	17	Roller application or brushing Equipment cleaning and maintenance (worker)	Page 66
	18	Roller application or brushing Equipment cleaning and maintenance (worker)	Page 66
	19	Non industrial spraying Spraying/fogging by manual application (worker)	Page 67
	20	Non industrial spraying Spraying/fogging by manual application (worker)	Page 67
	21	Non industrial spraying Spraying/fogging by manual application (worker)	Page 68
	22	Non industrial spraying Spraying/fogging by manual application (worker)	Page 68
	23	Treatment of articles by dipping and pouring Dipping, immersion and pouring (worker)	Page 69
	24	Production of preparations or articles by tableting, compression, extrusion, pelletisation (worker)	Page 69
	25	Production of preparations or articles by tableting, compression, extrusion, pelletisation (worker)	Page 70
	26	Use in laboratory reagents, Laboratory activities (small scale) (worker)	Page 70
	27	Hand-mixing with intimate contact and only PPE available (PPE) Hand application - Finger paints, Pastels, adhesives (worker)	Page 70
	28	Hand-mixing with intimate contact and only PPE available (PPE) Hand application - Finger paints, Pastels, adhesives (worker)	Page 71

Contributing exposure scenario 1

### Use in closed process, no likelihood of exposure General exposures (closed systems) (worker)

#### List of use descriptors

Process categories [PROC]:

PROC1: Use in closed process, no likelihood of exposure

#### Exposure prediction

Exposure estimation and reference to its source:

inhalative: 0.01 ppm  
dermal: 0.34 mg/kg/d

Risk characterisation ratio (RCR):

RCR: 0.002  
inhalative: 0.00002  
dermal: 0.002  
all relevant routes: 0.002

#### Risk management measures

Technical conditions and measures at process level (source) to prevent release:

Sample via a closed loop or other system to avoid exposure. Handle substance within a closed system.

Operational conditions and risk management measures:

(closed systems); Process sampling

Conditions and measures related to personal protection, hygiene and health evaluation:

Use personal protective equipment as required.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 59 of 121

Contributing exposure scenario 2

### **Use in closed, continuous process with occasional controlled exposure General exposures (closed systems) (worker)**

#### **List of use descriptors**

Process categories [PROC]:

PROC2: Use in closed, continuous process with occasional controlled exposure

#### **Exposure prediction**

Exposure estimation and reference to its source:

inhalative: 50 ppm

dermal: 1.37 mg/kg/d

Risk characterisation ratio (RCR):

RCR: 0.11

inhalative: 0.10

dermal: 0.01

all relevant routes: 0.11

#### **Risk management measures**

Technical conditions and measures at process level (source) to prevent release:

Sample via a closed loop or other system to avoid exposure. Handle substance within a closed system.

Operational conditions and risk management measures:

Continuous process; Process sampling

Conditions and measures related to personal protection, hygiene and health evaluation:

Use personal protective equipment as required.

Contributing exposure scenario 3

### **Use in closed batch process (synthesis or formulation) General exposures (closed systems) (worker)**

#### **List of use descriptors**

Process categories [PROC]:

PROC3: Use in closed batch process (synthesis or formulation)

#### **Exposure prediction**

Exposure estimation and reference to its source:

inhalative: 100 ppm

dermal: 0.34 mg/kg/d

Risk characterisation ratio (RCR):

RCR: 0.2

inhalative: 0.20

dermal: 0.002

all relevant routes: 0.20

#### **Risk management measures**

Technical conditions and measures at process level (source) to prevent release:

Sample via a closed loop or other system to avoid exposure. Handle substance within a closed system.

Operational conditions and risk management measures:

Batch process. Process sampling

Conditions and measures related to personal protection, hygiene and health evaluation:

Use personal protective equipment as required.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 60 of 121

Contributing exposure scenario 4

### **Use in batch and other process (synthesis) where opportunity for exposure arises Process sampling (open systems) (worker)**

#### **List of use descriptors**

Process categories [PROC]:

PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises

#### **Exposure prediction**

Exposure estimation and reference to its source:

inhalative: 250 ppm  
dermal: 6.86 mg/kg/d

Risk characterisation ratio (RCR):

RCR: 0.54  
inhalative: 0.50  
dermal: 0.04  
all relevant routes: 0.54

#### **Risk management measures**

Conditions and measures related to personal protection, hygiene and health evaluation:

Use personal protective equipment as required.

Contributing exposure scenario 5

### **Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact) Mixing operations (open systems) (worker)**

#### **List of use descriptors**

Process categories [PROC]:

PROC5: Mixing or blending in batch processes

#### **Exposure prediction**

Exposure estimation and reference to its source:

inhalative: 100 ppm (local exhaust ventilation - efficiency of at least [%]: 80)  
dermal: 0.07 mg/kg/d (local exhaust ventilation - efficiency of at least [%]: 99)

Risk characterisation ratio (RCR):

RCR: 0.2  
inhalative: 0.20  
dermal: 0.00  
all relevant routes: 0.20

#### **Risk management measures**

Technical conditions and measures at process level (source) to prevent release:

Ensure material transfers are under containment or extract ventilation.

Operational conditions and risk management measures:

Batch process;  
Process sampling;  
with local exhaust ventilation

Conditions and measures related to personal protection, hygiene and health evaluation:

Use personal protective equipment as required.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 61 of 121

Contributing exposure scenario 6

### Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)

### Mixing operations (open systems) (worker)

#### List of use descriptors

Process categories [PROC]:

PROC5: Mixing or blending in batch processes

#### Exposure prediction

Exposure estimation and reference to its source:

inhalative: 350 ppm (dilution ventilation effectiveness: 30 %)

dermal: 13.71 mg/kg/d

Risk characterisation ratio (RCR):

RCR: 0.77

inhalative: 0.70

dermal: 0.07

all relevant routes: 0.77

#### Risk management measures

Technical conditions and measures at process level (source) to prevent release:

Ensure operation is undertaken outdoors.

Operational conditions and risk management measures:

Batch process

Process sampling

Conditions and measures related to personal protection, hygiene and health evaluation:

Use personal protective equipment as required.

Contributing exposure scenario 7

### Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)

### Mixing operations (open systems) (worker)

#### List of use descriptors

Process categories [PROC]:

PROC5: Mixing or blending in batch processes

#### Exposure prediction

Exposure estimation and reference to its source:

inhalative: 300 ppm (exposure duration: 1 - 4 h)

dermal: 13.71 mg/kg/d

Risk characterisation ratio (RCR):

RCR: 0.67

inhalative: 0.60

dermal: 0.07

all relevant routes: 0.67

#### Risk management measures

Technical conditions and measures at process level (source) to prevent release:

Avoid carrying out activities involving exposure for more than 4 h.

Operational conditions and risk management measures:

Batch process

Process sampling

Conditions and measures related to personal protection, hygiene and health evaluation:

Use personal protective equipment as required.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 62 of 121

Contributing exposure scenario 8

### Calendering operations

#### Calendering (including Banburys); with local exhaust ventilation (worker)

##### List of use descriptors

Process categories [PROC]:

PROC6: Calendering operations

##### Exposure prediction

Exposure estimation and reference to its source:

inhalative: 420 ppm (local exhaust ventilation - efficiency of at least [%]: 80)

dermal: 27.43 mg/kg/d (local exhaust ventilation - efficiency of at least [%]: 95)

Risk characterisation ratio (RCR):

RCR: 0.99

inhalative: 0.84

dermal: 0.15

all relevant routes: 0.99

##### Risk management measures

Operational conditions and risk management measures:

Ensure operation is undertaken outdoors.

Conditions and measures related to personal protection, hygiene and health evaluation:

Use personal protective equipment as required.

Contributing exposure scenario 9

### Calendering operations

#### Calendering (including Banburys) (worker)

##### List of use descriptors

Process categories [PROC]:

PROC6: Calendering operations

##### Exposure prediction

Exposure estimation and reference to its source:

inhalative: 420 ppm (dilution ventilation effectiveness: 30 %)

dermal: 27.43 mg/kg/d

Risk characterisation ratio (RCR):

RCR: 0.99

inhalative: 0.84

dermal: 0.15

all relevant routes: 0.99

##### Risk management measures

Operational conditions and risk management measures:

Ensure operation is undertaken outdoors.

Conditions and measures related to personal protection, hygiene and health evaluation:

Use personal protective equipment as required.

Contributing exposure scenario 10

### Calendering operations

#### Calendering (including Banburys) (worker)

##### List of use descriptors

Process categories [PROC]:

PROC6: Calendering operations

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 63 of 121

### Exposure prediction

Exposure estimation and reference to its source:

inhalative: 360 ppm (exposure duration: 1 - 4 h)

dermal: 27.43 mg/kg/d

Risk characterisation ratio (RCR):

RCR: 0.87

inhalative: 0.72

dermal: 0.15

all relevant routes: 0.87

### Risk management measures

Operational conditions and risk management measures:

Avoid carrying out activities involving exposure for more than 4 h.

Conditions and measures related to personal protection, hygiene and health evaluation:

Use personal protective equipment as required.

Contributing exposure scenario 11

### Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

#### Bulk transfers (worker)

#### List of use descriptors

Process categories [PROC]:

PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

### Exposure prediction

Exposure estimation and reference to its source:

inhalative: 100 ppm (local exhaust ventilation - efficiency of at least [%]: 80)

dermal: 0.14 mg/kg/d (local exhaust ventilation - efficiency of at least [%]: 99)

Risk characterisation ratio (RCR):

RCR: 0.2

inhalative: 0.20

dermal: 0.001

all relevant routes: 0.20

### Risk management measures

Technical conditions and measures at process level (source) to prevent release:

Ensure material transfers are under containment or extract ventilation.

Operational conditions and risk management measures:

Non-dedicated facility

Transfer from/pouring from containers

with local exhaust ventilation

Conditions and measures related to personal protection, hygiene and health evaluation:

Use personal protective equipment as required.

Contributing exposure scenario 12

### Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

#### Bulk transfers (worker)

#### List of use descriptors

Process categories [PROC]:

PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 64 of 121

### Exposure prediction

Exposure estimation and reference to its source:

inhalative: 350 ppm (dilution ventilation effectiveness: 30 %)

dermal: 13.71 mg/kg/d

Risk characterisation ratio (RCR):

RCR: 0.77

inhalative: 0.70

dermal: 0.07

all relevant routes: 0.77

### Risk management measures

Technical conditions and measures at process level (source) to prevent release:

Ensure operation is undertaken outdoors.

Operational conditions and risk management measures:

Non-dedicated facility

Transfer from/pouring from containers

Conditions and measures related to personal protection, hygiene and health evaluation:

Use personal protective equipment as required.

Contributing exposure scenario 13

**Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities**

**Bulk transfers (worker)**

### List of use descriptors

Process categories [PROC]:

PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

### Exposure prediction

Exposure estimation and reference to its source:

inhalative: 300 ppm (exposure duration: 1 - 4 h)

dermal: 13.71 mg/kg/d

Risk characterisation ratio (RCR):

RCR: 0.67

inhalative: 0.60

dermal: 0.07

all relevant routes: 0.67

### Risk management measures

Technical conditions and measures at process level (source) to prevent release:

Avoid carrying out activities involving exposure for more than 4 h.

Operational conditions and risk management measures:

Non-dedicated facility

Transfer from/pouring from containers

Conditions and measures related to personal protection, hygiene and health evaluation:

Use personal protective equipment as required.

Contributing exposure scenario 14

**Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities**

**Bulk transfers (worker)**

### List of use descriptors

Process categories [PROC]:

PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 65 of 121

### Exposure prediction

Exposure estimation and reference to its source:

inhalative: 250 ppm  
dermal: 6.86 mg/kg/d

Risk characterisation ratio (RCR):

RCR: 0.54  
inhalative: 0.50  
dermal: 0.04  
all relevant routes: 0.54

### Risk management measures

Operational conditions and risk management measures:

Dedicated facility  
Transfer from/pouring from containers

Conditions and measures related to personal protection, hygiene and health evaluation:

Use personal protective equipment as required.

Contributing exposure scenario 15

### Transfer of substance or preparation into small containers (dedicated filling line, including weighing) Small package filling (worker)

#### List of use descriptors

Process categories [PROC]:

PROC9: Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

### Exposure prediction

Exposure estimation and reference to its source:

inhalative: 250 ppm  
dermal: 6.86 mg/kg/d

Risk characterisation ratio (RCR):

RCR: 0.54  
inhalative: 0.50  
dermal: 0.04  
all relevant routes: 0.54

### Risk management measures

Operational conditions and risk management measures:

Dedicated facility;  
Pouring from small containers

Conditions and measures related to personal protection, hygiene and health evaluation:

Use personal protective equipment as required.

Contributing exposure scenario 16

### Roller application or brushing Equipment cleaning and maintenance (worker)

#### List of use descriptors

Process categories [PROC]:

PROC10: Roller application or brushing

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 66 of 121

### Exposure prediction

Exposure estimation and reference to its source:

inhalative: 100 ppm (local exhaust ventilation - efficiency of at least [%]: 80)  
dermal: 1.37 mg/kg/d (local exhaust ventilation - efficiency of at least [%]: 95)

Risk characterisation ratio (RCR):

RCR: 0.21  
inhalative: 0.20  
dermal: 0.007  
all relevant routes: 0.21

### Risk management measures

Technical conditions and measures at process level (source) to prevent release:

Ensure material transfers are under containment or extract ventilation.

Operational conditions and risk management measures:

Or: Equipment cleaning and maintenance; with local exhaust ventilation

Conditions and measures related to personal protection, hygiene and health evaluation:

Use personal protective equipment as required.

Contributing exposure scenario 17

### Roller application or brushing Equipment cleaning and maintenance (worker)

#### List of use descriptors

Process categories [PROC]:

PROC10: Roller application or brushing

### Exposure prediction

Exposure estimation and reference to its source:

inhalative: 300 ppm (TRA Concentration factor 5 - 25 %)  
dermal: 16.46 mg/kg/d (TRA Concentration factor 5 - 25 %)

Risk characterisation ratio (RCR):

RCR: 0.69  
inhalative: 0.60  
dermal: 0.09  
all relevant routes: 0.69

### Risk management measures

Technical conditions and measures at process level (source) to prevent release:

Limit the substance content in the product to 25 %.

Operational conditions and risk management measures:

Or: Equipment cleaning and maintenance

Conditions and measures related to personal protection, hygiene and health evaluation:

Use personal protective equipment as required.

Contributing exposure scenario 18

### Roller application or brushing Equipment cleaning and maintenance (worker)

#### List of use descriptors

Process categories [PROC]:

PROC10: Roller application or brushing

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 67 of 121

### Exposure prediction

Exposure estimation and reference to its source:

inhalative: 300 ppm (exposure duration: 1-4 h)

dermal: 27.43 mg/kg/d

Risk characterisation ratio (RCR):

RCR: 0.75

inhalative: 0.60

dermal: 0.15

all relevant routes: 0.75

### Risk management measures

Technical conditions and measures at process level (source) to prevent release:

Avoid carrying out activities involving exposure for more than 4 h.

Operational conditions and risk management measures:

Or: Equipment cleaning and maintenance

Conditions and measures related to personal protection, hygiene and health evaluation:

Use personal protective equipment as required.

Contributing exposure scenario 19

### Non industrial spraying

#### Spraying/fogging by manual application (worker)

##### List of use descriptors

Process categories [PROC]:

PROC11: Non industrial spraying

### Exposure prediction

Exposure estimation and reference to its source:

inhalative: 200 ppm (local exhaust ventilation - efficiency of at least [%]: 80)

dermal: 2.14 mg/kg/d (local exhaust ventilation - efficiency of at least [%]: 98)

Risk characterisation ratio (RCR):

RCR: 0.41

inhalative: 0.40

dermal: 0.01

all relevant routes: 0.41

### Risk management measures

Technical conditions and measures at process level (source) to prevent release:

Ensure material transfers are under containment or extract ventilation.

Operational conditions and risk management measures:

with local exhaust ventilation

Conditions and measures related to personal protection, hygiene and health evaluation:

Use personal protective equipment as required.

Contributing exposure scenario 20

### Non industrial spraying

#### Spraying/fogging by manual application (worker)

##### List of use descriptors

Process categories [PROC]:

PROC11: Non industrial spraying

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 68 of 121

### Exposure prediction

Exposure estimation and reference to its source:

inhalative: 252 ppm (local exhaust ventilation - efficiency of at least [%]: 30; TRA  
Concentration factor 5 - 25 %; Exposure duration: 1-4 h)  
dermal: 64.28 mg/kg/d (TRA Concentration factor 5 - 25 %)

Risk characterisation ratio (RCR):

RCR: 0.85  
inhalative: 0.50  
dermal: 0.35  
all relevant routes: 0.85

### Risk management measures

Technical conditions and measures at process level (source) to prevent release:

Limit the substance content in the product to 25 %. Ensure operation is undertaken outdoors. Avoid carrying out activities involving exposure for more than 4 h.

Conditions and measures related to personal protection, hygiene and health evaluation:

Use personal protective equipment as required.

---

Contributing exposure scenario 21

### Non industrial spraying

#### Spraying/fogging by manual application (worker)

##### List of use descriptors

Process categories [PROC]:

PROC11: Non industrial spraying

### Exposure prediction

Exposure estimation and reference to its source:

inhalative: 200 ppm (Exposure duration: 15 min - 1 h)  
dermal: 107.14 mg/kg/d

Risk characterisation ratio (RCR):

RCR: 0.98  
inhalative: 0.40  
dermal: 0.58  
all relevant routes: 0.98

### Risk management measures

Technical conditions and measures at process level (source) to prevent release:

Avoid carrying out activities involving exposure for more than 1 h.

Conditions and measures related to personal protection, hygiene and health evaluation:

Use personal protective equipment as required.

---

Contributing exposure scenario 22

### Non industrial spraying

#### Spraying/fogging by manual application (worker)

##### List of use descriptors

Process categories [PROC]:

PROC11: Non industrial spraying

### Exposure prediction

Exposure estimation and reference to its source:

inhalative: 100 ppm (Respiratory protective device, efficiency of 90%)  
dermal: 107.14 mg/kg/d

Risk characterisation ratio (RCR):

RCR: 0.78  
inhalative: 0.20  
dermal: 0.58  
all relevant routes: 0.78

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 69 of 121

### Risk management measures

Conditions and measures related to personal protection, hygiene and health evaluation:

Wear a respirator conforming to EN140 with Type A filter or better.

Contributing exposure scenario 23

### Treatment of articles by dipping and pouring

#### Dipping, immersion and pouring (worker)

#### List of use descriptors

Process categories [PROC]:

PROC13: Treatment of articles by dipping and pouring

#### Exposure prediction

Exposure estimation and reference to its source:

inhalative: 250 ppm  
dermal: 13.71 mg/kg/d

Risk characterisation ratio (RCR):

RCR: 0.57  
inhalative: 0.50  
dermal: 0.07  
all relevant routes: 0.57

### Risk management measures

Conditions and measures related to personal protection, hygiene and health evaluation:

Use personal protective equipment as required.

Contributing exposure scenario 24

### Production of preparations or articles by tableting, compression, extrusion, pelletisation (worker)

#### List of use descriptors

Process categories [PROC]:

PROC14: Production of preparations or articles by tableting, compression, extrusion, pelletisation

#### Exposure prediction

Exposure estimation and reference to its source:

inhalative: 100 ppm (local exhaust ventilation - efficiency of at least [%]: 80)  
dermal: 0.34 mg/kg/d (local exhaust ventilation - efficiency of at least [%]: 90)

Risk characterisation ratio (RCR):

RCR: 0.2  
inhalative: 0.20  
dermal: 0.002  
all relevant routes: 0.20

### Risk management measures

Technical conditions and measures at process level (source) to prevent release:

Ensure material transfers are under containment or extract ventilation.

Operational conditions and risk management measures:

with local exhaust ventilation

Conditions and measures related to personal protection, hygiene and health evaluation:

Use personal protective equipment as required.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 70 of 121

Contributing exposure scenario 25

### Production of preparations or articles by tableting, compression, extrusion, pelletisation (worker)

#### List of use descriptors

Process categories [PROC]:

PROC14: Production of preparations or articles by tableting, compression, extrusion, pelletisation

#### Exposure prediction

Exposure estimation and reference to its source:

inhalative: 300 ppm (TRA exposure duration 1 - 4 h)

dermal: 3.43 mg/kg/d (local exhaust ventilation - efficiency of at least [%]: 90)

Risk characterisation ratio (RCR):

RCR: 0.62

inhalative: 0.60

dermal: 0.02

all relevant routes: 0.62

#### Risk management measures

Technical conditions and measures at process level (source) to prevent release:

Avoid carrying out activities involving exposure for more than 4 h.

Operational conditions and risk management measures:

with local exhaust ventilation

Conditions and measures related to personal protection, hygiene and health evaluation:

Use personal protective equipment as required.

Contributing exposure scenario 26

### Use in laboratory reagents, Laboratory activities (small scale) (worker)

#### List of use descriptors

Process categories [PROC]:

PROC15: Use as laboratory reagent

#### Exposure prediction

Exposure estimation and reference to its source:

inhalative: 50 ppm

dermal: 0.34 mg/kg/d

Risk characterisation ratio (RCR):

RCR: 0.1

inhalative: 0.10

dermal: 0.002

all relevant routes: 0.10

#### Risk management measures

Conditions and measures related to personal protection, hygiene and health evaluation:

Use personal protective equipment as required.

Contributing exposure scenario 27

### Hand-mixing with intimate contact and only PPE available (PPE)

### Hand application - Finger paints, Pastels, adhesives (worker)

#### List of use descriptors

Process categories [PROC]:

PROC19: Hand-mixing with intimate contact and only PPE available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 71 of 121

### Exposure prediction

Exposure estimation and reference to its source:

inhalative: 300 ppm (TRA Concentration factor 5 - 25 %)

dermal: 16.97 mg/kg/d (TRA Concentration factor 5 - 25 %; Gloves)

Risk characterisation ratio (RCR):

RCR: 0.96

inhalative: 0.60

dermal: 0.09

all relevant routes: 0.69

### Risk management measures

Technical conditions and measures at process level (source) to prevent release:

Limit the substance content in the product to 25 %.

Conditions and measures related to personal protection, hygiene and health evaluation:

Wear suitable gloves tested to EN374.

Contributing exposure scenario 28

### Hand-mixing with intimate contact and only PPE available (PPE)

### Hand application - Finger paints, Pastels, adhesives (worker)

### List of use descriptors

Process categories [PROC]:

PROC19: Hand-mixing with intimate contact and only PPE available

### Exposure prediction

Exposure estimation and reference to its source:

inhalative: 100 ppm (TRA exposure duration 15 min - 1 h)

dermal: 141.43 mg/kg/d

Risk characterisation ratio (RCR):

RCR: 0.96

inhalative: 0.20

dermal: 0.76

all relevant routes: 0.96

### Risk management measures

Technical conditions and measures at process level (source) to prevent release:

Avoid carrying out activities involving exposure for more than 1h.

Conditions and measures related to personal protection, hygiene and health evaluation:

Use personal protective equipment as required.

### Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

not applicable

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 72 of 121

### Exposure Scenario 13: Use in laboratories

#### List of use descriptors

Sector of uses [SU]: SU22: Professional uses

#### Application

Activities and processes: Use of small quantities within laboratory settings, including material transfers and equipment cleaning

Remark: Process categories [PROC]  
PROC10, PROC15  
Process Categories (additionally): PROC19

Control of worker exposure:  
See section risk management measures

Human Health, Worker exposure and risk assessment:  
Exposure assessment and method: Shown are the result of the quantitative exposure and risk assessment prepared based on the 'GES Worker Chemical Safety Assessment (CSA) Template'. This tool can be downloaded from the CEFIC website:  
<http://cefic.org/templates/shwPublications.asp?HID=750>

Examples for Environmental release categories [ERC]:  
ERC8a

Environment, ECT acetone:  
Please use the 'ECT Acetone' to check your local conditions. The Excel-tool enables the performance of scaling calculation for specific local environmental conditions. It can be downloaded from the web page of the Phenol & Derivatives REACH-consortium:  
<http://www.reachcentrum.eu/EN/consortium-management/consortia-under-reach/phenol-derivatives-reach-consortium.aspx>

Guidance to check compliance with the exposure scenario: Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Contributing Scenarios:	1	General information Applies to all contributing exposure scenarios related to exposure scenario 13: Use in laboratories (environment)	Page 72
	2	General information Applies to all contributing exposure scenarios related to exposure scenario 13: Use in laboratories (worker)	Page 73

Contributing exposure scenario 1

#### General information

**Applies to all contributing exposure scenarios related to exposure scenario 13: Use in laboratories (environment)**

#### List of use descriptors

Environmental release categories [ERC]:  
ERC8a: wide dispersive indoor use of processing aids in open systems

#### Operational conditions

Product characteristics: Substance is a unique structure, ketone, readily biodegradable  
Amounts used:  
Annual site tonnage Please use the Excel-Tool 'ECT Acetone' to calculate your maximum tonnage/year.

Duration and frequency of use:  
360 d/y

Other relevant operational conditions:  
Indoor/Outdoor use



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 73 of 121

### Exposure prediction

Exposure estimation and reference to its source:

Common practices vary across sites thus conservative process release estimates used.  
Please use the 'ECT Acetone' to check your local conditions.

Risk characterisation ratio (RCR):

ECT Acetone

### Risk management measures

Technical conditions and measures at process level (source) to prevent release:

Common practices vary across sites thus conservative process release estimates used.  
Typical technical measures are closed systems or scrubbers or charcoal adsorbers.  
Treat air emission to provide a typical removal efficiency of (%): 90

### Disposal considerations

Conditions and measures related to sewage treatment plant:

Please use the Excel-Tool 'ECT Acetone' to check your local conditions.

Conditions and measures related to external treatment of waste for disposal:

External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste:

External treatment and disposal of waste should comply with applicable local and/or national regulations.

Contributing exposure scenario 2

### General information

**Applies to all contributing exposure scenarios related to exposure scenario 13: Use in laboratories (worker)**

### List of use descriptors

Process categories [PROC]:

PROC10: Roller application or brushing

PROC15: Use as laboratory reagent

PROC19: Hand-mixing with intimate contact and only PPE available

### Operational conditions

Product characteristics: liquid, vapour pressure > 10 kPa

Concentration of the substance in a mixture:

Covers percentage substance in the product up to 100 % (unless stated differently.)

Duration and frequency of use:

Covers daily exposures up to 8h (unless stated differently)

Other relevant operational conditions:

Assumes a good basic standard of occupational hygiene is implemented.

### Exposure prediction

Exposure estimation and reference to its source:

refer to GES No. 12 professional

Risk characterisation ratio (RCR):

refer to GES No. 12 professional

### Risk management measures

Conditions and measures related to information and behavioural advice to consumers:

Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan.

Operational conditions and risk management measures:

Locate bulk storage outdoors.

Conditions and measures related to personal protection, hygiene and health evaluation:

Use suitable eye protection.

If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to EN374 and provide employee skin care programmes.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 74 of 121

### **Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES**

'ECT Acetone': The Excel-tool enables the performance of scaling calculation for specific local environmental conditions. It can be downloaded from the web page of the Phenol & Derivatives REACH-consortium:  
<http://www.reachcentrum.eu/EN/consortium-management/consortia-under-reach/phenol-derivatives-reach-consortium.aspx>

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 75 of 121

### Exposure Scenario 14: Uses in coatings

#### List of use descriptors

Sector of uses [SU]: SU22: Professional uses

#### Application

Remark: Process categories [PROC]  
PROC5, PROC 8a, PROC10, PROC13  
Process Categories (additionally): PROC1, PROC2, PROC3, PROC4, PROC8b,  
PROC9, PROC11, PROC15, PROC19  
Control of worker exposure:  
See section risk management measures  
Human Health, Worker exposure and risk assessment:  
Exposure assessment and method: Shown are the result of the quantitative exposure  
and risk assessment prepared based on the 'GES Worker Chemical Safety Assessment  
(CSA) Template'. This tool can be downloaded from the CEFIC website:  
<http://cefic.org/templates/shwPublications.asp?HID=750>

Examples for Environmental release categories [ERC]:  
ERC8a, ERC8c, ERC8d, ERC8f

Environment, ECT acetone:

Please use the 'ECT Acetone' to check your local conditions. The Excel-tool enables the  
performance of scaling calculation for specific local environmental conditions. It can be  
downloaded from the web page of the Phenol & Derivatives REACH-consortium:  
<http://www.reachcentrum.eu/EN/consortium-management/consortia-under-reach/phenol-derivatives-reach-consortium.aspx>

Guidance to check compliance with the exposure scenario: Guidance is based on  
assumed operating conditions which may not be applicable to all sites; thus, scaling  
may be necessary to define appropriate site-specific risk management measures.

Contributing Scenarios:	1	General information Applies to all contributing exposure scenarios related to exposure scenario 14: Uses in coatings (environment)	Page 75
	2	General information Applies to all contributing exposure scenarios related to exposure scenario 14: Uses in coatings (worker)	Page 76

Contributing exposure scenario 1

#### General information

**Applies to all contributing exposure scenarios related to exposure scenario 14: Uses in coatings (environment)**

#### List of use descriptors

Environmental release categories [ERC]:

ERC8a: wide dispersive indoor use of processing aids in open systems  
ERC8c: Wide dispersive indoor use resulting in inclusion into or onto a matrix  
ERC8d: wide dispersive outdoor use of processing aids in open systems  
ERC8f: Wide dispersive outdoor use resulting in inclusion into or onto a matrix

#### Operational conditions

Product characteristics: Substance is a unique structure, ketone, readily biodegradable

Amounts used:

Annual site tonnage Please use the Excel-Tool 'ECT Acetone'  
to calculate your maximum tonnage/year.

Duration and frequency of use:

360 d/y

Other relevant operational conditions:

Indoor/Outdoor use

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 76 of 121

### Exposure prediction

Exposure estimation and reference to its source:

Common practices vary across sites thus conservative process release estimates used.  
Please use the 'ECT Acetone' to check your local conditions.

Risk characterisation ratio (RCR):

ECT Acetone

### Risk management measures

Technical conditions and measures at process level (source) to prevent release:

Common practices vary across sites thus conservative process release estimates used.  
Typical technical measures are closed systems or scrubbers or charcoal adsorbers.  
Treat air emission to provide a typical removal efficiency of (%): 90

Operational conditions and risk management measures:

Common practices vary across sites thus conservative process release estimates used.  
Please use the 'ECT Acetone' to check your local conditions.

### Disposal considerations

Conditions and measures related to sewage treatment plant:

Please use the Excel-Tool 'ECT Acetone' to check your local conditions.

Conditions and measures related to external treatment of waste for disposal:

External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste:

External treatment and disposal of waste should comply with applicable local and/or national regulations.

Contributing exposure scenario 2

### General information

**Applies to all contributing exposure scenarios related to exposure scenario 14:**

#### Uses in coatings (worker)

#### List of use descriptors

Process categories [PROC]:

PROC5: Mixing or blending in batch processes  
PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities  
PROC10: Roller application or brushing  
PROC13: Treatment of articles by dipping and pouring  
PROC1: Use in closed process, no likelihood of exposure  
PROC2: Use in closed, continuous process with occasional controlled exposure  
PROC3: Use in closed batch process (synthesis or formulation)  
PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises  
PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities  
PROC9: Transfer of substance or mixture into small containers (dedicated filling line, including weighing)  
PROC11: Non industrial spraying  
PROC15: Use as laboratory reagent  
PROC19: Hand-mixing with intimate contact and only PPE available

### Operational conditions

Product characteristics: liquid, vapour pressure > 10 kPa

Concentration of the substance in a mixture:

Covers percentage substance in the product up to 100 % (unless stated differently.)

Duration and frequency of use:

Covers daily exposures up to 8h (unless stated differently)

Other relevant operational conditions:

Assumes a good basic standard of occupational hygiene is implemented.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 77 of 121

### Exposure prediction

Exposure estimation and reference to its source:

refer to GES No. 12 professional

Risk characterisation ratio (RCR):

refer to GES No. 12 professional

### Risk management measures

Conditions and measures related to information and behavioural advice to consumers:

Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan.

Operational conditions and risk management measures:

Locate bulk storage outdoors.

Conditions and measures related to personal protection, hygiene and health evaluation:

Use suitable eye protection.

If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to EN374 and provide employee skin care programmes.

### Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

'ECT Acetone': The Excel-tool enables the performance of scaling calculation for specific local environmental conditions. It can be downloaded from the web page of the Phenol & Derivatives REACH-consortium:

<http://www.reachcentrum.eu/EN/consortium-management/consortia-under-reach/phenol-derivatives-reach-consortium.aspx>

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 78 of 121

### Exposure Scenario 15: Use in binders and release agents

#### List of use descriptors

Sector of uses [SU]: SU22: Professional uses

#### Application

Activities and processes: Covers the use as binders and release agents including material transfers, mixing, application (including spraying and brushing), mould forming and casting and handling of waste

Remark: Process categories [PROC]  
PROC1, PROC2, PROC3, PROC4, PROC5, PROC6, PROC8a, PROC8b, PROC9, PROC10, PROC11  
Control of worker exposure:  
See section risk management measures  
Human Health, Worker exposure and risk assessment:  
Exposure assessment and method: Shown are the result of the quantitative exposure and risk assessment prepared based on the 'GES Worker Chemical Safety Assessment (CSA) Template'. This tool can be downloaded from the CEFIC website:  
<http://cefic.org/templates/shwPublications.asp?HID=750>

Examples for Environmental release categories [ERC]:  
ERC8a, ERC8b, ERC8c, ERC8d, ERC8e, ERC8f

Environment, ECT acetone:  
Please use the 'ECT Acetone' to check your local conditions. The Excel-tool enables the performance of scaling calculation for specific local environmental conditions. It can be downloaded from the web page of the Phenol & Derivatives REACH-consortium:  
<http://www.reachcentrum.eu/EN/consortium-management/consortia-under-reach/phenol-derivatives-reach-consortium.aspx>

Guidance to check compliance with the exposure scenario: Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Contributing Scenarios:	1	General information Applies to all contributing exposure scenarios related to exposure scenario 15: Use in binders and release agents (environment)	Page 78
	2	General information Applies to all contributing exposure scenarios related to exposure scenario 15: Use in binders and release agents (worker)	Page 79

Contributing exposure scenario 1

#### General information

**Applies to all contributing exposure scenarios related to exposure scenario 15: Use in binders and release agents (environment)**

#### List of use descriptors

Environmental release categories [ERC]:

ERC8a: wide dispersive indoor use of processing aids in open systems  
ERC8b: Wide dispersive indoor use of reactive substances in open systems  
ERC8c: Wide dispersive indoor use resulting in inclusion into or onto a matrix  
ERC8d: wide dispersive outdoor use of processing aids in open systems  
ERC8e: Wide dispersive outdoor use of reactive substances in open systems  
ERC8f: Wide dispersive outdoor use resulting in inclusion into or onto a matrix

#### Operational conditions

Product characteristics: Substance is a unique structure, ketone, readily biodegradable  
Amounts used:  
Annual site tonnage Please use the Excel-Tool 'ECT Acetone' to calculate your maximum tonnage/year.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 79 of 121

Duration and frequency of use:

360 d/y

Other relevant operational conditions:

Indoor/Outdoor use

### Exposure prediction

Exposure estimation and reference to its source:

Common practices vary across sites thus conservative process release estimates used.  
Please use the 'ECT Acetone' to check your local conditions.

Risk characterisation ratio (RCR):

ECT Acetone

### Risk management measures

Technical conditions and measures at process level (source) to prevent release:

Common practices vary across sites thus conservative process release estimates used.  
Typical technical measures are closed systems or scrubbers or charcoal adsorbers.  
Treat air emission to provide a typical removal efficiency of (%): 90

### Disposal considerations

Conditions and measures related to sewage treatment plant:

Please use the Excel-Tool 'ECT Acetone' to check your local conditions.

Conditions and measures related to external treatment of waste for disposal:

External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste:

External treatment and disposal of waste should comply with applicable local and/or national regulations.

Contributing exposure scenario 2

### General information

**Applies to all contributing exposure scenarios related to exposure scenario 15: Use in binders and release agents (worker)**

### List of use descriptors

Process categories [PROC]:

- PROC1: Use in closed process, no likelihood of exposure
- PROC2: Use in closed, continuous process with occasional controlled exposure
- PROC3: Use in closed batch process (synthesis or formulation)
- PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises
- PROC5: Mixing or blending in batch processes
- PROC6: Calendering operations
- PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities
- PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities
- PROC9: Transfer of substance or mixture into small containers (dedicated filling line, including weighing)
- PROC10: Roller application or brushing
- PROC11: Non industrial spraying

### Operational conditions

Product characteristics: liquid, vapour pressure > 10 kPa

Concentration of the substance in a mixture:

Covers percentage substance in the product up to 100 % (unless stated differently.)

Duration and frequency of use:

Covers daily exposures up to 8h (unless stated differently)

Other relevant operational conditions:

Assumes a good basic standard of occupational hygiene is implemented.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 80 of 121

### Exposure prediction

Exposure estimation and reference to its source:

refer to GES No. 12 professional

Risk characterisation ratio (RCR):

refer to GES No. 12 professional

### Risk management measures

Technical conditions and measures at process level (source) to prevent release:

Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan.

Operational conditions and risk management measures:

Locate bulk storage outdoors.

Conditions and measures related to personal protection, hygiene and health evaluation:

Use suitable eye protection.

If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to EN374 and provide employee skin care programmes.

### Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

'ECT Acetone': The Excel-tool enables the performance of scaling calculation for specific local environmental conditions. It can be downloaded from the web page of the Phenol & Derivatives REACH-consortium:

<http://www.reachcentrum.eu/EN/consortium-management/consortia-under-reach/phenol-derivatives-reach-consortium.aspx>



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 81 of 121

### Exposure Scenario 16: Polymer production

#### List of use descriptors

Sector of uses [SU]: SU22: Professional uses

#### Application

Activities and processes: Manufacturing of formulated polymers  
Remark: Process categories [PROC]: PROC8a  
Process Categories (additionally): PROC1, PROC2, PROC8b, PROC9, PROC14  
Control of worker exposure:  
See section risk management measures  
Human Health, Worker exposure and risk assessment:  
Exposure assessment and method: Shown are the result of the quantitative exposure and risk assessment prepared based on the 'GES Worker Chemical Safety Assessment (CSA) Template'. This tool can be downloaded from the CEFIC website:  
<http://cefic.org/templates/shwPublications.asp?HID=750>

Examples for Environmental release categories [ERC]:

ERC8a, ERC8d, ERC8c, ERC8f

Environment, ECT acetone:

Please use the 'ECT Acetone' to check your local conditions. The Excel-tool enables the performance of scaling calculation for specific local environmental conditions. It can be downloaded from the web page of the Phenol & Derivatives REACH-consortium:  
<http://www.reachcentrum.eu/EN/consortium-management/consortia-under-reach/phenol-derivatives-reach-consortium.aspx>

Guidance to check compliance with the exposure scenario: Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Contributing Scenarios:	1	General information Applies to all contributing exposure scenarios related to exposure scenario 16: Polymer production (environment)	Page 81
	2	General information Applies to all contributing exposure scenarios related to exposure scenario 16: Polymer production (worker)	Page 82

Contributing exposure scenario 1

#### General information

**Applies to all contributing exposure scenarios related to exposure scenario 16: Polymer production (environment)**

#### List of use descriptors

Environmental release categories [ERC]:

ERC8a: wide dispersive indoor use of processing aids in open systems

ERC8d: wide dispersive outdoor use of processing aids in open systems

ERC8c: Wide dispersive indoor use resulting in inclusion into or onto a matrix

ERC8f: Wide dispersive outdoor use resulting in inclusion into or onto a matrix

#### Operational conditions

Product characteristics: Substance is a unique structure, ketone, readily biodegradable

Amounts used:

Annual site tonnage Please use the Excel-Tool 'ECT Acetone' to calculate your maximum tonnage/year.

Duration and frequency of use:

360 d/y

Other relevant operational conditions:

Indoor/Outdoor use

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 82 of 121

### Exposure prediction

Exposure estimation and reference to its source:

Common practices vary across sites thus conservative process release estimates used.  
Please use the 'ECT Acetone' to check your local conditions.

Risk characterisation ratio (RCR):

ECT Acetone

### Risk management measures

Technical conditions and measures at process level (source) to prevent release:

Common practices vary across sites thus conservative process release estimates used.  
Typical technical measures are closed systems or scrubbers or charcoal adsorbers.  
Treat air emission to provide a typical removal efficiency of (%): 90 %

### Disposal considerations

Conditions and measures related to sewage treatment plant:

Please use the Excel-Tool 'ECT Acetone' to check your local conditions.

Conditions and measures related to external treatment of waste for disposal:

External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste:

External treatment and disposal of waste should comply with applicable local and/or national regulations.

Contributing exposure scenario 2

### General information

**Applies to all contributing exposure scenarios related to exposure scenario 16:**

### Polymer production (worker)

#### List of use descriptors

Process categories [PROC]:

PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

PROC1: Use in closed process, no likelihood of exposure

PROC2: Use in closed, continuous process with occasional controlled exposure

PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

PROC9: Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

PROC14: Production of preparations or articles by tableting, compression, extrusion, pelletisation

#### Operational conditions

Product characteristics: liquid, vapour pressure > 10 kPa

Concentration of the substance in a mixture:

Covers percentage substance in the product up to 100 % (unless stated differently.)

Duration and frequency of use:

Covers daily exposures up to 8h (unless stated differently)

Other relevant operational conditions:

Assumes a good basic standard of occupational hygiene is implemented.

#### Exposure prediction

Exposure estimation and reference to its source:

refer to GES No. 12 professional

Risk characterisation ratio (RCR):

refer to GES No. 12 professional

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

**INEOS Phenol**

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 83 of 121

### Risk management measures

Technical conditions and measures at process level (source) to prevent release:

Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan.

Operational conditions and risk management measures:

Locate bulk storage outdoors.

Conditions and measures related to personal protection, hygiene and health evaluation:

Use suitable eye protection.

If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to EN374 and provide employee skin care programmes.

### Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

'ECT Acetone': The Excel-tool enables the performance of scaling calculation for specific local environmental conditions. It can be downloaded from the web page of the Phenol & Derivatives REACH-consortium:

<http://www.reachcentrum.eu/EN/consortium-management/consortia-under-reach/phenol-derivatives-reach-consortium.aspx>

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 84 of 121

### Exposure Scenario 17: Polymer processing

#### List of use descriptors

Sector of uses [SU]: SU22: Professional uses

#### Application

Activities and processes: Processing of formulated polymers including material transfers, moulding and forming activities, material re-works and associated maintenance

Remark: Process categories [PROC]: PROC8a  
Process Categories (additionally): PROC1, PROC2, PROC8b, PROC9, PROC14  
Control of worker exposure:  
See section risk management measures  
Human Health, Worker exposure and risk assessment:  
Exposure assessment and method: Shown are the result of the quantitative exposure and risk assessment prepared based on the 'GES Worker Chemical Safety Assessment (CSA) Template'. This tool can be downloaded from the CEFIC website:  
<http://cefic.org/templates/shwPublications.asp?HID=750>  
Examples for Environmental release categories [ERC]:  
ERC8a, ERC8d, ERC8c, ERC8f  
Environment, ECT acetone:  
Please use the 'ECT Acetone' to check your local conditions. The Excel-tool enables the performance of scaling calculation for specific local environmental conditions. It can be downloaded from the web page of the Phenol & Derivatives REACH-consortium:  
<http://www.reachcentrum.eu/EN/consortium-management/consortia-under-reach/phenol-derivatives-reach-consortium.aspx>  
Guidance to check compliance with the exposure scenario: Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Contributing Scenarios:	1	General information Applies to all contributing exposure scenarios related to exposure scenario 17: Polymer processing (environment)	Page 84
	2	General information Applies to all contributing exposure scenarios related to exposure scenario 17: Polymer processing (worker)	Page 85

Contributing exposure scenario 1

#### General information

**Applies to all contributing exposure scenarios related to exposure scenario 17: Polymer processing (environment)**

#### List of use descriptors

Environmental release categories [ERC]:

ERC8a: wide dispersive indoor use of processing aids in open systems  
ERC8d: wide dispersive outdoor use of processing aids in open systems  
ERC8c: Wide dispersive indoor use resulting in inclusion into or onto a matrix  
ERC8f: Wide dispersive outdoor use resulting in inclusion into or onto a matrix

#### Operational conditions

Product characteristics: Substance is a unique structure, ketone, readily biodegradable  
Amounts used:  
Annual site tonnage Please use the Excel-Tool 'ECT Acetone' to calculate your maximum tonnage/year.

Duration and frequency of use:  
360 d/y

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 85 of 121

Other relevant operational conditions:

Indoor/Outdoor use

### Exposure prediction

Exposure estimation and reference to its source:

Common practices vary across sites thus conservative process release estimates used.  
Please use the 'ECT Acetone' to check your local conditions.

Risk characterisation ratio (RCR):

ECT Acetone

### Risk management measures

Technical conditions and measures at process level (source) to prevent release:

Common practices vary across sites thus conservative process release estimates used.  
Typical technical measures are closed systems or scrubbers or charcoal adsorbers.  
Treat air emission to provide a typical removal efficiency of (%): 90 %

### Disposal considerations

Conditions and measures related to sewage treatment plant:

Please use the Excel-Tool 'ECT Acetone' to check your local conditions.

Conditions and measures related to external treatment of waste for disposal:

External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste:

External treatment and disposal of waste should comply with applicable local and/or national regulations.

Contributing exposure scenario 2

### General information

**Applies to all contributing exposure scenarios related to exposure scenario 17:  
Polymer processing (worker)**

### List of use descriptors

Process categories [PROC]:

PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

PROC1: Use in closed process, no likelihood of exposure

PROC2: Use in closed, continuous process with occasional controlled exposure

PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

PROC9: Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

PROC14: Production of preparations or articles by tableting, compression, extrusion, pelletisation

### Operational conditions

Product characteristics: liquid, vapour pressure > 10 kPa

Concentration of the substance in a mixture:

Covers percentage substance in the product up to 100 % (unless stated differently.)

Duration and frequency of use:

Covers daily exposures up to 8h (unless stated differently)

Other relevant operational conditions:

Assumes a good basic standard of occupational hygiene is implemented.

### Exposure prediction

Exposure estimation and reference to its source:

refer to GES No. 12 professional

Risk characterisation ratio (RCR):

refer to GES No. 12 professional

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 86 of 121

### Risk management measures

Technical conditions and measures at process level (source) to prevent release:

Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan.

Operational conditions and risk management measures:

Locate bulk storage outdoors.

Conditions and measures related to personal protection, hygiene and health evaluation:

Use suitable eye protection.

If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to EN374 and provide employee skin care programmes.

### Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

'ECT Acetone': The Excel-tool enables the performance of scaling calculation for specific local environmental conditions. It can be downloaded from the web page of the Phenol & Derivatives REACH-consortium:

<http://www.reachcentrum.eu/EN/consortium-management/consortia-under-reach/phenol-derivatives-reach-consortium.aspx>

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 87 of 121

### Exposure Scenario 18: Use in cleaning agents

#### List of use descriptors

Sector of uses [SU]: SU22: Professional uses

#### Application

Activities and processes: Covers the use as a component of cleaning products including pouring/unloading from drums or containers and exposures during mixing/diluting in the preparatory phase and cleaning activities (including spraying, brushing, dipping, wiping, automated and by hand).

Remark: Process categories [PROC]  
PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9, PROC10, PROC11, PROC13, PROC19

Control of worker exposure:  
See section risk management measures

Human Health, Worker exposure and risk assessment:  
Exposure assessment and method: Shown are the result of the quantitative exposure and risk assessment prepared based on the 'GES Worker Chemical Safety Assessment (CSA) Template'. This tool can be downloaded from the CEFIC website:  
<http://cefic.org/templates/shwPublications.asp?HID=750>

Examples for Environmental release categories [ERC]:  
ERC8a, Environmental release categories (additionally): ERC8d

Environment, ECT acetone:  
Please use the 'ECT Acetone' to check your local conditions. The Excel-tool enables the performance of scaling calculation for specific local environmental conditions. It can be downloaded from the web page of the Phenol & Derivatives REACH-consortium:  
<http://www.reachcentrum.eu/EN/consortium-management/consortia-under-reach/phenol-derivatives-reach-consortium.aspx>

Guidance to check compliance with the exposure scenario: Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Contributing Scenarios:	1	General information Applies to all contributing exposure scenarios related to exposure scenario 18: Use in cleaning agents (environment)	Page 87
	2	General information Applies to all contributing exposure scenarios related to exposure scenario 18: Use in cleaning agents (worker)	Page 88

Contributing exposure scenario 1

#### General information

**Applies to all contributing exposure scenarios related to exposure scenario 18:  
Use in cleaning agents (environment)**

#### List of use descriptors

Environmental release categories [ERC]:  
ERC8a: wide dispersive indoor use of processing aids in open systems

#### Operational conditions

Product characteristics: Substance is a unique structure, ketone, readily biodegradable  
Amounts used:  
Annual site tonnage Please use the Excel-Tool 'ECT Acetone' to calculate your maximum tonnage/year.

Duration and frequency of use:  
360 d/y

Other relevant operational conditions:  
Indoor/Outdoor use

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 88 of 121

### Exposure prediction

Exposure estimation and reference to its source:

Common practices vary across sites thus conservative process release estimates used.  
Please use the 'ECT Acetone' to check your local conditions.

Risk characterisation ratio (RCR):

ECT Acetone

### Risk management measures

Technical conditions and measures at process level (source) to prevent release:

Common practices vary across sites thus conservative process release estimates used.  
Typical technical measures are closed systems or scrubbers or charcoal adsorbers.  
Treat air emission to provide a typical removal efficiency of (%): 90

### Disposal considerations

Conditions and measures related to sewage treatment plant:

Please use the Excel-Tool 'ECT Acetone' to check your local conditions.

Conditions and measures related to external treatment of waste for disposal:

External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste:

External treatment and disposal of waste should comply with applicable local and/or national regulations.

Contributing exposure scenario 2

### General information

**Applies to all contributing exposure scenarios related to exposure scenario 18:**

**Use in cleaning agents (worker)**

### List of use descriptors

Process categories [PROC]:

- PROC1: Use in closed process, no likelihood of exposure
- PROC2: Use in closed, continuous process with occasional controlled exposure
- PROC3: Use in closed batch process (synthesis or formulation)
- PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises
- PROC5: Mixing or blending in batch processes
- PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities
- PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities
- PROC9: Transfer of substance or mixture into small containers (dedicated filling line, including weighing)
- PROC10: Roller application or brushing
- PROC11: Non industrial spraying
- PROC13: Treatment of articles by dipping and pouring
- PROC19: Hand-mixing with intimate contact and only PPE available

### Operational conditions

Product characteristics: liquid, vapour pressure > 10 kPa

Concentration of the substance in a mixture:

Covers percentage substance in the product up to 100 % (unless stated differently.)

Duration and frequency of use:

Covers daily exposures up to 8h (unless stated differently)

Other relevant operational conditions:

Assumes a good basic standard of occupational hygiene is implemented.

### Exposure prediction

Exposure estimation and reference to its source:

refer to GES No. 12 professional

Risk characterisation ratio (RCR):

refer to GES No. 12 professional



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

**INEOS Phenol**

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 89 of 121

### Risk management measures

Technical conditions and measures at process level (source) to prevent release:

Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan.

Operational conditions and risk management measures:

Locate bulk storage outdoors.

Conditions and measures related to personal protection, hygiene and health evaluation:

Use suitable eye protection.

If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to EN374 and provide employee skin care programmes.

### Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

'ECT Acetone': The Excel-tool enables the performance of scaling calculation for specific local environmental conditions. It can be downloaded from the web page of the Phenol & Derivatives REACH-consortium:

<http://www.reachcentrum.eu/EN/consortium-management/consortia-under-reach/phenol-derivatives-reach-consortium.aspx>

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 90 of 121

### Exposure Scenario 19: Oil field well drilling and production operations

#### List of use descriptors

Sector of uses [SU]: SU22: Professional uses

#### Application

Activities and processes: Covers the use as a component of cleaning products including pouring/unloading from drums or containers

Remark: Process categories [PROC]  
PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b

Control of worker exposure:  
See section risk management measures

Human Health, Worker exposure and risk assessment:  
Exposure assessment and method: Shown are the result of the quantitative exposure and risk assessment prepared based on the 'GES Worker Chemical Safety Assessment (CSA) Template'. This tool can be downloaded from the CEFIC website:  
<http://cefic.org/templates/shwPublications.asp?HID=750>

Examples for Environmental release categories [ERC]:  
ERC8d

Environment, ECT acetone:  
Please use the 'ECT Acetone' to check your local conditions. The Excel-tool enables the performance of scaling calculation for specific local environmental conditions. It can be downloaded from the web page of the Phenol & Derivatives REACH-consortium:  
<http://www.reachcentrum.eu/EN/consortium-management/consortia-under-reach/phenol-derivatives-reach-consortium.aspx>

Guidance to check compliance with the exposure scenario: Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Contributing Scenarios:	1	General information Applies to all contributing exposure scenarios related to exposure scenario 19: Oil field well drilling and production operations (environment)	Page 90
	2	General information Applies to all contributing exposure scenarios related to exposure scenario 19: Oil field well drilling and production operations (worker)	Page 91

Contributing exposure scenario 1

#### General information

**Applies to all contributing exposure scenarios related to exposure scenario 19: Oil field well drilling and production operations (environment)**

#### List of use descriptors

Environmental release categories [ERC]:  
ERC8d: wide dispersive outdoor use of processing aids in open systems

#### Operational conditions

Product characteristics: Substance is a unique structure, ketone, readily biodegradable  
Amounts used:  
Annual site tonnage Please use the Excel-Tool 'ECT Acetone' to calculate your maximum tonnage/year.

Duration and frequency of use:  
360 d/y

Other relevant operational conditions:  
Indoor/Outdoor use

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 91 of 121

### Exposure prediction

Exposure estimation and reference to its source:

Common practices vary across sites thus conservative process release estimates used.  
Please use the 'ECT Acetone' to check your local conditions.

Risk characterisation ratio (RCR):

ECT Acetone

### Risk management measures

Technical conditions and measures at process level (source) to prevent release:

Common practices vary across sites thus conservative process release estimates used.  
Typical technical measures are closed systems or scrubbers or charcoal adsorbers.  
Treat air emission to provide a typical removal efficiency of (%): 90 %

### Disposal considerations

Conditions and measures related to sewage treatment plant:

Please use the Excel-Tool 'ECT Acetone' to check your local conditions.

Conditions and measures related to external treatment of waste for disposal:

External treatment and disposal of waste should comply with applicable local and/or national regulations.

Contributing exposure scenario 2

### General information

**Applies to all contributing exposure scenarios related to exposure scenario 19: Oil field well drilling and production operations (worker)**

### List of use descriptors

Process categories [PROC]:

PROC1: Use in closed process, no likelihood of exposure  
PROC2: Use in closed, continuous process with occasional controlled exposure  
PROC3: Use in closed batch process (synthesis or formulation)  
PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises  
PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities  
PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

### Operational conditions

Product characteristics: liquid, vapour pressure > 10 kPa

Concentration of the substance in a mixture:

Covers percentage substance in the product up to 100 % (unless stated differently.)

Duration and frequency of use:

Covers daily exposures up to 8h (unless stated differently)

Other relevant operational conditions:

Assumes a good basic standard of occupational hygiene is implemented.

### Exposure prediction

Exposure estimation and reference to its source:

refer to GES No. 12 professional

Risk characterisation ratio (RCR):

refer to GES No. 12 professional

### Risk management measures

Technical conditions and measures at process level (source) to prevent release:

Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan.

Operational conditions and risk management measures:

Locate bulk storage outdoors.

Conditions and measures related to personal protection, hygiene and health evaluation:

Use suitable eye protection.

If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to EN374 and provide employee skin care programmes.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 92 of 121

### **Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES**

'ECT Acetone': The Excel-tool enables the performance of scaling calculation for specific local environmental conditions. It can be downloaded from the web page of the Phenol & Derivatives REACH-consortium:  
<http://www.reachcentrum.eu/EN/consortium-management/consortia-under-reach/phenol-derivatives-reach-consortium.aspx>

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 93 of 121

### Exposure Scenario 20: Agrochemical uses

#### List of use descriptors

Sector of uses [SU]: SU22: Professional uses

#### Application

Activities and processes: Use as an agrochemical excipient for application by manual or machine spraying, smokes and fogging; including equipment clean-downs and disposal.

Remark: Process categories [PROC]  
PROC1, PROC2, PROC4, PROC8a, PROC8b, PROC11, PROC13, PROC19

Control of worker exposure:

See section risk management measures

Human Health, Worker exposure and risk assessment:

Exposure assessment and method: Shown are the result of the quantitative exposure and risk assessment prepared based on the 'GES Worker Chemical Safety Assessment (CSA) Template'. This tool can be downloaded from the CEFIC website:  
<http://cefic.org/templates/shwPublications.asp?HID=750>

Examples for Environmental release categories [ERC]:  
ERC8a, ERC8d

Environment, ECT acetone:

Please use the 'ECT Acetone' to check your local conditions. The Excel-tool enables the performance of scaling calculation for specific local environmental conditions. It can be downloaded from the web page of the Phenol & Derivatives REACH-consortium:  
<http://www.reachcentrum.eu/EN/consortium-management/consortia-under-reach/phenol-derivatives-reach-consortium.aspx>

Guidance to check compliance with the exposure scenario: Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Contributing Scenarios:	1	General information Applies to all contributing exposure scenarios related to exposure scenario 20: Agrochemical uses (environment)	Page 93
	2	General information Applies to all contributing exposure scenarios related to exposure scenario 20: Agrochemical uses (worker)	Page 94

Contributing exposure scenario 1

#### General information

**Applies to all contributing exposure scenarios related to exposure scenario 20: Agrochemical uses (environment)**

#### List of use descriptors

Environmental release categories [ERC]:

ERC8a: wide dispersive indoor use of processing aids in open systems

ERC8d: wide dispersive outdoor use of processing aids in open systems

#### Operational conditions

Product characteristics: Substance is a unique structure, ketone, readily biodegradable

Amounts used:

Annual site tonnage Please use the Excel-Tool 'ECT Acetone' to calculate your maximum tonnage/year.

Duration and frequency of use:

360 d/y

Other relevant operational conditions:

Indoor/Outdoor use

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 94 of 121

### Exposure prediction

Exposure estimation and reference to its source:

Common practices vary across sites thus conservative process release estimates used.  
Please use the 'ECT Acetone' to check your local conditions.

Risk characterisation ratio (RCR):

ECT Acetone

### Risk management measures

Technical conditions and measures at process level (source) to prevent release:

Common practices vary across sites thus conservative process release estimates used.  
Typical technical measures are closed systems or scrubbers or charcoal adsorbers.  
Treat air emission to provide a typical removal efficiency of (%): 90

### Disposal considerations

Conditions and measures related to sewage treatment plant:

Please use the Excel-Tool 'ECT Acetone' to check your local conditions.

Conditions and measures related to external treatment of waste for disposal:

External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste:

External treatment and disposal of waste should comply with applicable local and/or national regulations.

Contributing exposure scenario 2

### General information

**Applies to all contributing exposure scenarios related to exposure scenario 20:**

### Agrochemical uses (worker)

### List of use descriptors

Process categories [PROC]:

PROC1: Use in closed process, no likelihood of exposure

PROC2: Use in closed, continuous process with occasional controlled exposure

PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises

PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

PROC11: Non industrial spraying

PROC13: Treatment of articles by dipping and pouring

PROC19: Hand-mixing with intimate contact and only PPE available

### Operational conditions

Product characteristics: liquid, vapour pressure > 10 kPa

Concentration of the substance in a mixture:

Covers percentage substance in the product up to 100 % (unless stated differently.)

Duration and frequency of use:

Covers daily exposures up to 8h (unless stated differently)

Other relevant operational conditions:

Assumes a good basic standard of occupational hygiene is implemented.

### Exposure prediction

Exposure estimation and reference to its source:

refer to GES No. 12 professional

Risk characterisation ratio (RCR):

refer to GES No. 12 professional

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

**INEOS Phenol**

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 95 of 121

### Risk management measures

Technical conditions and measures at process level (source) to prevent release:

Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan.

Operational conditions and risk management measures:

Locate bulk storage outdoors.

Conditions and measures related to personal protection, hygiene and health evaluation:

Use suitable eye protection.

If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to EN374 and provide employee skin care programmes.

### Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

'ECT Acetone': The Excel-tool enables the performance of scaling calculation for specific local environmental conditions. It can be downloaded from the web page of the Phenol & Derivatives REACH-consortium:

<http://www.reachcentrum.eu/EN/consortium-management/consortia-under-reach/phenol-derivatives-reach-consortium.aspx>

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 96 of 121

### Exposure Scenario 21: De-icing and anti-icing applications

#### List of use descriptors

Sector of uses [SU]: SU22: Professional uses

#### Application

Activities and processes: Ice prevention and de-icing of vehicles, aircraft and other equipment by spraying.

Remark: Process categories [PROC]  
PROC1, PROC2, PROC8b, PROC11, PROC19

Control of worker exposure:  
See section risk management measures

Human Health, Worker exposure and risk assessment:  
Exposure assessment and method: Shown are the result of the quantitative exposure and risk assessment prepared based on the 'GES Worker Chemical Safety Assessment (CSA) Template'. This tool can be downloaded from the CEFIC website:  
<http://cefic.org/templates/shwPublications.asp?HID=750>

Examples for Environmental release categories [ERC]:  
ERC8d

Environment, ECT acetone:  
Please use the 'ECT Acetone' to check your local conditions. The Excel-tool enables the performance of scaling calculation for specific local environmental conditions. It can be downloaded from the web page of the Phenol & Derivatives REACH-consortium:  
<http://www.reachcentrum.eu/EN/consortium-management/consortia-under-reach/phenol-derivatives-reach-consortium.aspx>

Guidance to check compliance with the exposure scenario: Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Contributing Scenarios:	1	General information Applies to all contributing exposure scenarios related to exposure scenario 21: De-icing and anti-icing applications (environment)	Page 96
	2	General information Applies to all contributing exposure scenarios related to exposure scenario 21: De-icing and anti-icing applications (worker)	Page 97

Contributing exposure scenario 1

#### General information

**Applies to all contributing exposure scenarios related to exposure scenario 21: De-icing and anti-icing applications (environment)**

#### List of use descriptors

Environmental release categories [ERC]:  
ERC8d: wide dispersive outdoor use of processing aids in open systems

#### Operational conditions

Product characteristics: Substance is a unique structure, ketone, readily biodegradable

Amounts used:  
Annual site tonnage Please use the Excel-Tool 'ECT Acetone' to calculate your maximum tonnage/year.

Duration and frequency of use:  
360 d/y

Other relevant operational conditions:  
Indoor/Outdoor use



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 97 of 121

### Exposure prediction

Exposure estimation and reference to its source:

Common practices vary across sites thus conservative process release estimates used.  
Please use the 'ECT Acetone' to check your local conditions.

Risk characterisation ratio (RCR):

ECT Acetone

### Risk management measures

Technical conditions and measures at process level (source) to prevent release:

Common practices vary across sites thus conservative process release estimates used.  
Typical technical measures are closed systems or scrubbers or charcoal adsorbers.  
Treat air emission to provide a typical removal efficiency of (%): 90

### Disposal considerations

Conditions and measures related to sewage treatment plant:

Please use the Excel-Tool 'ECT Acetone' to check your local conditions.

Conditions and measures related to external treatment of waste for disposal:

External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste:

External treatment and disposal of waste should comply with applicable local and/or national regulations.

Contributing exposure scenario 2

### General information

**Applies to all contributing exposure scenarios related to exposure scenario 21: De-icing and anti-icing applications (worker)**

### List of use descriptors

Process categories [PROC]:

PROC1: Use in closed process, no likelihood of exposure  
PROC2: Use in closed, continuous process with occasional controlled exposure  
PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities  
PROC11: Non industrial spraying  
PROC19: Hand-mixing with intimate contact and only PPE available

### Operational conditions

Product characteristics: liquid, vapour pressure > 10 kPa

Concentration of the substance in a mixture:

Covers percentage substance in the product up to 100 % (unless stated differently.)

Duration and frequency of use:

Covers daily exposures up to 8h (unless stated differently)

Other relevant operational conditions:

Assumes a good basic standard of occupational hygiene is implemented.

### Exposure prediction

Exposure estimation and reference to its source:

refer to GES No. 12 professional

Risk characterisation ratio (RCR):

refer to GES No. 12 professional

### Risk management measures

Technical conditions and measures at process level (source) to prevent release:

Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan.

Operational conditions and risk management measures:

Locate bulk storage outdoors.

Conditions and measures related to personal protection, hygiene and health evaluation:

Use suitable eye protection.

If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to EN374 and provide employee skin care programmes.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 98 of 121

### **Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES**

'ECT Acetone': The Excel-tool enables the performance of scaling calculation for specific local environmental conditions. It can be downloaded from the web page of the Phenol & Derivatives REACH-consortium:  
<http://www.reachcentrum.eu/EN/consortium-management/consortia-under-reach/phenol-derivatives-reach-consortium.aspx>

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 99 of 121

### Exposure Scenario 22: Explosives manufacture & use

#### List of use descriptors

Sector of uses [SU]: SU22: Professional uses

#### Application

Activities and processes: Covers exposures arising from the manufacture and use of slurry explosives including materials transfer, mixing and charging and equipment cleaning.

Remark: Process categories [PROC]  
PROC1, PROC3, PROC5, PROC8a, PROC8b

Control of worker exposure:  
See section risk management measures

Human Health, Worker exposure and risk assessment:  
Exposure assessment and method: Shown are the result of the quantitative exposure and risk assessment prepared based on the 'GES Worker Chemical Safety Assessment (CSA) Template'. This tool can be downloaded from the CEFIC website:  
<http://cefic.org/templates/shwPublications.asp?HID=750>

Examples for Environmental release categories [ERC]:  
ERC8d

Environment, ECT acetone:  
Please use the 'ECT Acetone' to check your local conditions. The Excel-tool enables the performance of scaling calculation for specific local environmental conditions. It can be downloaded from the web page of the Phenol & Derivatives REACH-consortium:  
<http://www.reachcentrum.eu/EN/consortium-management/consortia-under-reach/phenol-derivatives-reach-consortium.aspx>

Guidance to check compliance with the exposure scenario: Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Contributing Scenarios:	1	General information Applies to all contributing exposure scenarios related to exposure scenario 22: Explosives manufacture & use (environment)	Page 99
	2	General information Applies to all contributing exposure scenarios related to exposure scenario 22: Explosives manufacture & use (worker)	Page 100

Contributing exposure scenario 1

#### General information

**Applies to all contributing exposure scenarios related to exposure scenario 22: Explosives manufacture & use (environment)**

#### List of use descriptors

Environmental release categories [ERC]:  
ERC8d: wide dispersive outdoor use of processing aids in open systems

#### Operational conditions

Product characteristics: Substance is a unique structure, ketone, readily biodegradable

Amounts used:  
Annual site tonnage Please use the Excel-Tool 'ECT Acetone' to calculate your maximum tonnage/year.

Duration and frequency of use:  
360 d/y

Other relevant operational conditions:  
Indoor/Outdoor use

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 100 of 121

### Exposure prediction

Exposure estimation and reference to its source:

Common practices vary across sites thus conservative process release estimates used.  
Please use the 'ECT Acetone' to check your local conditions.

Risk characterisation ratio (RCR):

ECT Acetone

### Risk management measures

Technical conditions and measures at process level (source) to prevent release:

Common practices vary across sites thus conservative process release estimates used.  
Typical technical measures are closed systems or scrubbers or charcoal adsorbers.  
Treat air emission to provide a typical removal efficiency of (%): 90 %

### Disposal considerations

Conditions and measures related to sewage treatment plant:

Please use the Excel-Tool 'ECT Acetone' to check your local conditions.

Conditions and measures related to external treatment of waste for disposal:

External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste:

External treatment and disposal of waste should comply with applicable local and/or national regulations.

Contributing exposure scenario 2

### General information

**Applies to all contributing exposure scenarios related to exposure scenario 22:**

**Explosives manufacture & use (worker)**

### List of use descriptors

Process categories [PROC]:

PROC1: Use in closed process, no likelihood of exposure

PROC3: Use in closed batch process (synthesis or formulation)

PROC5: Mixing or blending in batch processes

PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

### Operational conditions

Product characteristics: liquid, vapour pressure > 10 kPa

Concentration of the substance in a mixture:

Covers percentage substance in the product up to 100 % (unless stated differently.)

Duration and frequency of use:

Covers daily exposures up to 8h (unless stated differently)

Other relevant operational conditions:

Assumes a good basic standard of occupational hygiene is implemented.

### Exposure prediction

Exposure estimation and reference to its source:

refer to GES No. 12 professional

Risk characterisation ratio (RCR):

refer to GES No. 12 professional

### Risk management measures

Technical conditions and measures at process level (source) to prevent release:

Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan.

Operational conditions and risk management measures:

Locate bulk storage outdoors.

Conditions and measures related to personal protection, hygiene and health evaluation:

Use suitable eye protection.

If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to EN374 and provide employee skin care programmes.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 101 of 121

---

### **Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES**

'ECT Acetone': The Excel-tool enables the performance of scaling calculation for specific local environmental conditions. It can be downloaded from the web page of the Phenol & Derivatives REACH-consortium:  
<http://www.reachcentrum.eu/EN/consortium-management/consortia-under-reach/phenol-derivatives-reach-consortium.aspx>

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 102 of 121

### Exposure Scenario 23: Generic exposure scenario (GES): Consumer uses of Acetone (ES 24 - 26)

#### List of use descriptors

Sector of uses [SU]: SU21: Consumer uses

#### Application

Activities and processes: Generic exposure scenario, applies to all contributing exposure scenarios related to exposure scenario 24 - 26 (consumer uses):

ES24 - Uses in coatings  
ES25 - Use in cleaning agents  
ES26 - De-icing and anti-icing applications

Contributing Scenarios:	1	Adhesives, sealants Glues, hobby use (Consumer)	Page 103
	2	Adhesives, sealants Glues DIY-use (Consumer)	Page 103
	3	Adhesives, sealants Glue from spray (Consumer)	Page 104
	4	Adhesives Sealants (Consumer)	Page 104
	5	Air care products Air care, instant action (aerosol sprays) (Consumer)	Page 105
	6	Air care products Air care, continuous action (solid and liquid) (Consumer)	Page 105
	7	Anti-freeze and de-icing products Washing car window (Consumer)	Page 106
	8	Anti-freeze and de-icing products Pouring into radiator (Consumer)	Page 106
	9	Anti-freeze and de-icing products Lock de-icer (Consumer)	Page 107
	10	Coatings and paints, fillers, putties, thinners Waterborne latex wall paint (Consumer)	Page 107
	11	Coatings and paints, fillers, putties, thinners Solvent rich, high solid, water borne paint (Consumer)	Page 108
	12	Coatings and paints, fillers, putties, thinners Aerosol spray can (Consumer)	Page 108
	13	Coatings and paints, fillers, putties, thinners Removers (paint-, glue-, wall paper-, sealant-remover) (Consumer)	Page 108
	14	Fillers, putties, plasters, modelling clay Fillers and putty (Consumer)	Page 109
	15	Fillers, putties, plasters, modelling clay Plasters and floor equalizers (Consumer)	Page 109
	16	Fillers, putties, plasters, modelling clay Modelling clay (Consumer)	Page 110
	17	Finger paints (Consumer)	Page 110
	18	Non-metal surface treatment products Solvent rich, high solid, water borne paint (Consumer)	Page 111
	19	Non-metal surface treatment products Aerosol spray can (Consumer)	Page 111
	20	Non-metal surface treatment products Removers (paint-, glue-, wall paper-, sealant-remover) (Consumer)	Page 111
	21	Lubricants, greases, release products Liquids (Consumer)	Page 112
	22	Lubricants, greases, release products Pastes (Consumer)	Page 112

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 103 of 121

Contributing Scenarios:	23	Lubricants, greases, release products Sprays (Consumer)	Page 113
	24	Polishes and wax blends Polishes, wax/cream (floor, furniture, shoes) (Consumer)	Page 113
	25	Polishes and wax blends Polishes, spray (furniture, shoes) (Consumer)	Page 114
	26	Washing and cleaning products (including solvent based products) Laundry and dish washing products (Consumer)	Page 114
	27	Washing and cleaning products (including solvent based products) Cleaners, liquids (all purpose cleaners, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners) (Consumer)	Page 115
	28	Washing and cleaning products (including solvent based products) Cleaners, trigger sprays (all purpose cleaners, sanitary products, glass cleaners) (Consumer)	Page 115
	29	Welding and soldering products, flux products (Consumer)	Page 116

Contributing exposure scenario 1

### Adhesives, sealants

#### Glues, hobby use (Consumer)

##### List of use descriptors

Product (Sub-)Categories: PC1: Adhesives, sealants

##### Operational conditions

Concentration of the substance in a mixture:

<= 30% (unless otherwise stated)

Duration and frequency of use:

Covers use up to 365 d/y

1 application per day.

For each use event, covers use amounts up to 4 h.

Other relevant operational conditions:

Covers use under typical household ventilation room size of 20 m<sup>3</sup>.

##### Exposure prediction

Exposure estimation and reference to its source:

Covers skin contact area up to 35.73 cm<sup>2</sup>.

For each use event, covers use amounts up to 9 g.

##### Risk management measures

Operational conditions and risk management measures:

No specific risk management measure identified beyond those operational conditions stated.

Contributing exposure scenario 2

### Adhesives, sealants

#### Glues DIY-use (Consumer)

##### List of use descriptors

Product (Sub-)Categories: PC1: Adhesives, sealants

##### Operational conditions

Concentration of the substance in a mixture:

<= 30% (unless otherwise stated)

Duration and frequency of use:

Covers use up to 1 d/y

1 application per day.

For each use event, covers use amounts up to 6 h.

Other relevant operational conditions:

Covers use under typical household ventilation room size of 20 m<sup>3</sup>.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 104 of 121

### Exposure prediction

Exposure estimation and reference to its source:

Covers skin contact area up to 110 cm<sup>2</sup>.  
For each use event, covers use amounts up to 6390 g.

### Risk management measures

Operational conditions and risk management measures:

No specific risk management measure identified beyond those operational conditions stated.

---

Contributing exposure scenario 3

### Adhesives, sealants

#### Glue from spray (Consumer)

##### List of use descriptors

Product (Sub-)Categories: PC1: Adhesives, sealants

##### Operational conditions

Concentration of the substance in a mixture:

<= 30% (unless otherwise stated)

Duration and frequency of use:

Covers use up to 6 d/y  
1 application per day.  
For each use event, covers use amounts up to 4 h.

Other relevant operational conditions:

Covers use under typical household ventilation room size of 20 m<sup>3</sup>.

### Exposure prediction

Exposure estimation and reference to its source:

Covers skin contact area up to 35.73 cm<sup>2</sup>.  
For each use event, covers use amounts up to 85.05 g.

### Risk management measures

Operational conditions and risk management measures:

No specific risk management measure identified beyond those operational conditions stated.

---

Contributing exposure scenario 4

### Adhesives

#### Sealants (Consumer)

##### List of use descriptors

Product (Sub-)Categories: PC1: Adhesives, sealants

##### Operational conditions

Concentration of the substance in a mixture:

<= 30% (unless otherwise stated)

Duration and frequency of use:

Covers use up to 365 d/y  
1 application per day.  
For each use event, covers use amounts up to 1 h.

Other relevant operational conditions:

Covers use under typical household ventilation room size of 20 m<sup>3</sup>.

### Exposure prediction

Exposure estimation and reference to its source:

Covers skin contact area up to 35.73 cm<sup>2</sup>.  
For each use event, covers use amounts up to 75 g.



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 105 of 121

### Risk management measures

Operational conditions and risk management measures:

No specific risk management measure identified beyond those operational conditions stated.

---

Contributing exposure scenario 5

### Air care products

#### Air care, instant action (aerosol sprays) (Consumer)

##### List of use descriptors

Product (Sub-)Categories: PC3: Air care products

##### Operational conditions

Concentration of the substance in a mixture:

<= 50 % (unless otherwise stated)

Duration and frequency of use:

Covers use up to 365 d/y

Covers use up to 4x/ per day.

For each use event, covers use amounts up to 0.25 h.

Other relevant operational conditions:

Covers use under typical household ventilation room size of 20 m<sup>3</sup>.

##### Exposure prediction

Exposure estimation and reference to its source:

For each use event, covers use amounts up to 0.1 g.

### Risk management measures

Operational conditions and risk management measures:

No specific risk management measure identified beyond those operational conditions stated.

---

Contributing exposure scenario 6

### Air care products

#### Air care, continuous action (solid and liquid) (Consumer)

##### List of use descriptors

Product (Sub-)Categories: PC3: Air care products

##### Operational conditions

Concentration of the substance in a mixture:

<= 10 % (unless otherwise stated)

Duration and frequency of use:

Covers use up to 365 d/y

1 application per day.

For each use event, covers use amounts up to 8.0 h.

Other relevant operational conditions:

Covers use under typical household ventilation room size of 20 m<sup>3</sup>.

##### Exposure prediction

Exposure estimation and reference to its source:

Covers skin contact area up to 35.70 cm<sup>2</sup>.

For each use event, covers use amounts up to 0.48 g.

### Risk management measures

Operational conditions and risk management measures:

No specific risk management measure identified beyond those operational conditions stated.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 106 of 121

Contributing exposure scenario 7

### Anti-freeze and de-icing products Washing car window (Consumer)

#### List of use descriptors

Product (Sub-)Categories: PC4: Anti-freeze and de-icing products

#### Operational conditions

Concentration of the substance in a mixture:

<= 1 % (unless otherwise stated)

Duration and frequency of use:

Covers use up to 365 d/y

1 application per day.

For each use event, covers use amounts up to 0.02 h.

Other relevant operational conditions:

Covers use in a one car garage (34m<sup>3</sup>) under typical ventilation. Covers use in room size of 34 m<sup>3</sup>. Covers use under typical household ventilation room size of 20 m<sup>3</sup>.

#### Exposure prediction

Exposure estimation and reference to its source:

For each use event, covers use amounts up to 0.5 g.

#### Risk management measures

Operational conditions and risk management measures:

No specific risk management measure identified beyond those operational conditions stated.

Contributing exposure scenario 8

### Anti-freeze and de-icing products Pouring into radiator (Consumer)

#### List of use descriptors

Product (Sub-)Categories: PC4: Anti-freeze and de-icing products

#### Operational conditions

Concentration of the substance in a mixture:

<= 10 % (unless otherwise stated)

Duration and frequency of use:

Covers use up to 365 d/y

1 application per day.

For each use event, covers use amounts up to 0.17 h.

Other relevant operational conditions:

Covers use in a one car garage (34m<sup>3</sup>) under typical ventilation. Covers use in room size of 34 m<sup>3</sup>.

#### Exposure prediction

Exposure estimation and reference to its source:

Covers skin contact area up to 428 cm<sup>2</sup>.

For each use event, covers use amounts up to 2000 g.

#### Risk management measures

Operational conditions and risk management measures:

No specific risk management measure identified beyond those operational conditions stated.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 107 of 121

Contributing exposure scenario 9

### Anti-freeze and de-icing products Lock de-icer (Consumer)

#### List of use descriptors

Product (Sub-)Categories: PC4: Anti-freeze and de-icing products

#### Operational conditions

Concentration of the substance in a mixture:

<= 50 % (unless otherwise stated)

Duration and frequency of use:

Covers use up to 365 d/y

1 application per day.

For each use event, covers use amounts up to 0.25 h.

Other relevant operational conditions:

Covers use in a one car garage (34m<sup>3</sup>) under typical ventilation. Covers use in room size of 34 m<sup>3</sup>.

#### Exposure prediction

Exposure estimation and reference to its source:

Covers skin contact area up to 214.40 cm<sup>2</sup>.

For each use event, covers use amounts up to 4 g.

#### Risk management measures

Operational conditions and risk management measures:

No specific risk management measure identified beyond those operational conditions stated.

Contributing exposure scenario 10

### Coatings and paints, fillers, putties, thinners Waterborne latex wall paint (Consumer)

#### List of use descriptors

Product (Sub-)Categories: PC9a: Coatings and paints, thinners, paint removers

#### Operational conditions

Concentration of the substance in a mixture:

<= 1.5 % (unless otherwise stated)

Duration and frequency of use:

Covers use up to 4 d/y

1 application per day.

For each use event, covers use amounts up to 2.20 h.

Other relevant operational conditions:

Covers use under typical household ventilation room size of 20 m<sup>3</sup>.

#### Exposure prediction

Exposure estimation and reference to its source:

Covers skin contact area up to 428.75 cm<sup>2</sup>.

For each use event, covers use amounts up to 2760 g.

#### Risk management measures

Operational conditions and risk management measures:

No specific risk management measure identified beyond those operational conditions stated.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 108 of 121

Contributing exposure scenario 11

### Coatings and paints, fillers, putties, thinners Solvent rich, high solid, water borne paint (Consumer)

#### List of use descriptors

Product (Sub-)Categories: PC9a: Coatings and paints, thinners, paint removers

#### Operational conditions

Concentration of the substance in a mixture:

<= 27.5 % (unless otherwise stated)

Duration and frequency of use:

Covers use up to 6 d/y

1 application per day.

For each use event, covers use amounts up to 2.20 h.

Other relevant operational conditions:

Covers use under typical household ventilation room size of 20 m<sup>3</sup>.

#### Exposure prediction

Exposure estimation and reference to its source:

Covers skin contact area up to 428.75 cm<sup>2</sup>.

For each use event, covers use amounts up to 744 g.

#### Risk management measures

Operational conditions and risk management measures:

No specific risk management measure identified beyond those operational conditions stated.

Contributing exposure scenario 12

### Coatings and paints, fillers, putties, thinners Aerosol spray can (Consumer)

#### List of use descriptors

Product (Sub-)Categories: PC9a: Coatings and paints, thinners, paint removers

#### Operational conditions

Concentration of the substance in a mixture:

<= 50 % (unless otherwise stated)

Duration and frequency of use:

Covers use up to 2 d/y

1 application per day.

For each use event, covers use amounts up to 0.33 h.

Other relevant operational conditions:

Covers use in a one car garage (34m<sup>3</sup>) under typical ventilation. Covers use in room size of 34 m<sup>3</sup>.

#### Exposure prediction

Exposure estimation and reference to its source:

For each use event, covers use amounts up to 215 g.

#### Risk management measures

Operational conditions and risk management measures:

No specific risk management measure identified beyond those operational conditions stated.

Contributing exposure scenario 13

### Coatings and paints, fillers, putties, thinners Removers (paint-, glue-, wall paper-, sealant-remover) (Consumer)

#### List of use descriptors

Product (Sub-)Categories: PC9a: Coatings and paints, thinners, paint removers

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 109 of 121

### Operational conditions

Concentration of the substance in a mixture:

<= 50 % (unless otherwise stated)

Duration and frequency of use:

Covers use up to 3 d/y

1 application per day.

For each use event, covers use amounts up to 2 h.

Other relevant operational conditions:

Covers use under typical household ventilation room size of 20 m<sup>3</sup>.

### Exposure prediction

Exposure estimation and reference to its source:

Covers skin contact area up to 857.50 cm<sup>2</sup>.

For each use event, covers use amounts up to 491 g.

### Risk management measures

Operational conditions and risk management measures:

No specific risk management measure identified beyond those operational conditions stated.

---

Contributing exposure scenario 14

## Fillers, putties, plasters, modelling clay

### Fillers and putty (Consumer)

#### List of use descriptors

Product (Sub-)Categories: PC9b: Fillers, putties, plasters, modelling clay

### Operational conditions

Concentration of the substance in a mixture:

<= 2 % (unless otherwise stated)

Duration and frequency of use:

Covers use up to 12 d/y

1 application per day.

For each use event, covers use amounts up to 4 h.

Other relevant operational conditions:

Covers use under typical household ventilation room size of 20 m<sup>3</sup>.

### Exposure prediction

Exposure estimation and reference to its source:

Covers skin contact area up to 35.73 cm<sup>2</sup>.

For each use event, covers use amounts up to 85 g.

### Risk management measures

Operational conditions and risk management measures:

No specific risk management measure identified beyond those operational conditions stated.

---

Contributing exposure scenario 15

## Fillers, putties, plasters, modelling clay

### Plasters and floor equalizers (Consumer)

#### List of use descriptors

Product (Sub-)Categories: PC9b: Fillers, putties, plasters, modelling clay

### Operational conditions

Concentration of the substance in a mixture:

<= 2 % (unless otherwise stated)

Duration and frequency of use:

Covers use up to 12 d/y

1 application per day.

For each use event, covers use amounts up to 2 h.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 110 of 121

Other relevant operational conditions:

Covers use under typical household ventilation room size of 20 m<sup>3</sup>.

### Exposure prediction

Exposure estimation and reference to its source:

Covers skin contact area up to 857.50 cm<sup>2</sup>.

For each use event, covers use amounts up to 13800 g.

### Risk management measures

Operational conditions and risk management measures:

No specific risk management measure identified beyond those operational conditions stated.

Contributing exposure scenario 16

## Fillers, putties, plasters, modelling clay Modelling clay (Consumer)

### List of use descriptors

Product (Sub-)Categories: PC9b: Fillers, putties, plasters, modelling clay

### Operational conditions

Concentration of the substance in a mixture:

<= 1 % (unless otherwise stated)

Duration and frequency of use:

Covers use up to 365 d/y

1 application per day.

### Exposure prediction

Exposure estimation and reference to its source:

Covers skin contact area up to 254.40 cm<sup>2</sup>.

For each use event, assumes swallowed amount of 1 g.

### Risk management measures

Operational conditions and risk management measures:

No specific risk management measure identified beyond those operational conditions stated.

Contributing exposure scenario 17

## Finger paints (Consumer)

### List of use descriptors

Product (Sub-)Categories: PC9c: Finger paints

### Operational conditions

Concentration of the substance in a mixture:

<= 50 % (unless otherwise stated)

Duration and frequency of use:

Covers use up to 365 d/y

1 application per day.

### Exposure prediction

Exposure estimation and reference to its source:

Covers skin contact area up to 254.40 cm<sup>2</sup>.

For each use event, assumes swallowed amount of 1.35 g.

### Risk management measures

Operational conditions and risk management measures:

No specific risk management measure identified beyond those operational conditions stated.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 111 of 121

Contributing exposure scenario 18

### **Non-metal surface treatment products Solvent rich, high solid, water borne paint (Consumer)**

#### **List of use descriptors**

Product (Sub-)Categories: PC15: Non-metal surface treatment products

#### **Operational conditions**

Concentration of the substance in a mixture:

<= 27.5 % (unless otherwise stated)

Duration and frequency of use:

Covers use up to 6 d/y

1 application per day.

For each use event, covers use amounts up to 2.2 h.

Other relevant operational conditions:

Covers use under typical household ventilation room size of 20 m<sup>3</sup>.

#### **Exposure prediction**

Exposure estimation and reference to its source:

Covers skin contact area up to 428.75 cm<sup>2</sup>.

For each use event, covers use amounts up to 744 g.

#### **Risk management measures**

Operational conditions and risk management measures:

No specific risk management measure identified beyond those operational conditions stated.

Contributing exposure scenario 19

### **Non-metal surface treatment products Aerosol spray can (Consumer)**

#### **List of use descriptors**

Product (Sub-)Categories: PC15: Non-metal surface treatment products

#### **Operational conditions**

Concentration of the substance in a mixture:

<= 50 % (unless otherwise stated)

Duration and frequency of use:

Covers use up to 2 d/y

1 application per day.

For each use event, covers use amounts up to 0.33 h.

Other relevant operational conditions:

Covers use in a one car garage (34m<sup>3</sup>) under typical ventilation. Covers use in room size of 34 m<sup>3</sup>.

#### **Exposure prediction**

Exposure estimation and reference to its source:

For each use event, covers use amounts up to 215 g.

#### **Risk management measures**

Operational conditions and risk management measures:

No specific risk management measure identified beyond those operational conditions stated.

Contributing exposure scenario 20

### **Non-metal surface treatment products Removers (paint-, glue-, wall paper-, sealant-remover) (Consumer)**

#### **List of use descriptors**

Product (Sub-)Categories: PC15: Non-metal surface treatment products

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 112 of 121

### Operational conditions

Concentration of the substance in a mixture:

<= 50 % (unless otherwise stated)

Duration and frequency of use:

Covers use up to 3 d/y

1 application per day.

For each use event, covers use amounts up to 2.00 h.

Other relevant operational conditions:

Covers use under typical household ventilation room size of 20 m<sup>3</sup>.

### Exposure prediction

Exposure estimation and reference to its source:

Covers skin contact area up to 857.50 cm<sup>2</sup>.

For each use event, covers use amounts up to 491 g.

### Risk management measures

Operational conditions and risk management measures:

No specific risk management measure identified beyond those operational conditions stated.

---

Contributing exposure scenario 21

## Lubricants, greases, release products

### Liquids (Consumer)

#### List of use descriptors

Product (Sub-)Categories: PC24: Lubricants, greases, release products

### Operational conditions

Concentration of the substance in a mixture:

<= 100 % (unless otherwise stated)

Duration and frequency of use:

Covers use up to 4 d/y

1 application per day.

For each use event, covers use amounts up to 0.17 h.

Other relevant operational conditions:

Covers use in a one car garage (34m<sup>3</sup>) under typical ventilation. Covers use in room size of 34 m<sup>3</sup>.

### Exposure prediction

Exposure estimation and reference to its source:

Covers skin contact area up to 468 cm<sup>2</sup>.

For each use event, covers use amounts up to 2200 g.

### Risk management measures

Operational conditions and risk management measures:

No specific risk management measure identified beyond those operational conditions stated.

---

Contributing exposure scenario 22

## Lubricants, greases, release products

### Pastes (Consumer)

#### List of use descriptors

Product (Sub-)Categories: PC24: Lubricants, greases, release products

### Operational conditions

Concentration of the substance in a mixture:

<= 20 % (unless otherwise stated)

Duration and frequency of use:

Covers use up to 10 d/y

1 application per day.



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

**INEOS Phenol**

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 113 of 121

Other relevant operational conditions:

Covers use under typical household ventilation room size of 20 m<sup>3</sup>.

### Exposure prediction

Exposure estimation and reference to its source:

Covers skin contact area up to 468 cm<sup>2</sup>.

For each use event, covers use amounts up to 34 g.

### Risk management measures

Operational conditions and risk management measures:

No specific risk management measure identified beyond those operational conditions stated.

Contributing exposure scenario 23

## Lubricants, greases, release products Sprays (Consumer)

### List of use descriptors

Product (Sub-)Categories: PC24: Lubricants, greases, release products

### Operational conditions

Concentration of the substance in a mixture:

<= 50 % (unless otherwise stated)

Duration and frequency of use:

Covers use up to 6 d/y

1 application per day.

For each use event, covers use amounts up to 0,17 h.

Other relevant operational conditions:

Covers use under typical household ventilation room size of 20 m<sup>3</sup>.

### Exposure prediction

Exposure estimation and reference to its source:

Covers skin contact area up to 428.75 cm<sup>2</sup>.

For each use event, covers use amounts up to 73 g.

### Risk management measures

Operational conditions and risk management measures:

No specific risk management measure identified beyond those operational conditions stated.

Contributing exposure scenario 24

## Polishes and wax blends Polishes, wax/cream (floor, furniture, shoes) (Consumer)

### List of use descriptors

Product (Sub-)Categories: PC31: Polishes and wax blends

### Operational conditions

Concentration of the substance in a mixture:

<= 50 % (unless otherwise stated)

Duration and frequency of use:

Covers use up to 29 d/y

1 application per day.

For each use event, covers use amounts up to 1.23 h.

Other relevant operational conditions:

Covers use under typical household ventilation room size of 20 m<sup>3</sup>.

### Exposure prediction

Exposure estimation and reference to its source:

Covers skin contact area up to 430 cm<sup>2</sup>.

For each use event, covers use amounts up to 142 g.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 114 of 121

### Risk management measures

Operational conditions and risk management measures:

No specific risk management measure identified beyond those operational conditions stated.

---

Contributing exposure scenario 25

### Polishes and wax blends

#### Polishes, spray (furniture, shoes) (Consumer)

##### List of use descriptors

Product (Sub-)Categories: PC31: Polishes and wax blends

##### Operational conditions

Concentration of the substance in a mixture:

<= 50 % (unless otherwise stated)

Duration and frequency of use:

Covers use up to 8 d/y

1 application per day.

For each use event, covers use amounts up to 0.33 h.

Other relevant operational conditions:

Covers use under typical household ventilation room size of 20 m<sup>3</sup>.

##### Exposure prediction

Exposure estimation and reference to its source:

Covers skin contact area up to 430 cm<sup>2</sup>.

For each use event, covers use amounts up to 35 g.

### Risk management measures

Operational conditions and risk management measures:

No specific risk management measure identified beyond those operational conditions stated.

---

Contributing exposure scenario 26

### Washing and cleaning products (including solvent based products)

#### Laundry and dish washing products (Consumer)

##### List of use descriptors

Product (Sub-)Categories: PC35: Washing and cleaning products

##### Operational conditions

Concentration of the substance in a mixture:

<= 5 % (unless otherwise stated)

Duration and frequency of use:

Covers use up to 365 d/y

1 application per day.

For each use event, covers use amounts up to 0.50 h.

Other relevant operational conditions:

Covers use under typical household ventilation room size of 20 m<sup>3</sup>.

##### Exposure prediction

Exposure estimation and reference to its source:

Covers skin contact area up to 857.50 cm<sup>2</sup>.

For each use event, covers use amounts up to 15 g.

### Risk management measures

Operational conditions and risk management measures:

No specific risk management measure identified beyond those operational conditions stated.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 115 of 121

Contributing exposure scenario 27

### **Washing and cleaning products (including solvent based products)**

**Cleaners, liquids (all purpose cleaners, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners) (Consumer)**

#### **List of use descriptors**

Product (Sub-)Categories: PC35: Washing and cleaning products

#### **Operational conditions**

Concentration of the substance in a mixture:

<= 5 % (unless otherwise stated)

Duration and frequency of use:

Covers use up to 128 d/y

1 application per day.

For each use event, covers use amounts up to 0.33 h.

Other relevant operational conditions:

Covers use under typical household ventilation room size of 20 m<sup>3</sup>.

#### **Exposure prediction**

Exposure estimation and reference to its source:

Covers skin contact area up to 857.50 cm<sup>2</sup>.

For each use event, covers use amounts up to 27 g.

#### **Risk management measures**

Operational conditions and risk management measures:

No specific risk management measure identified beyond those operational conditions stated.

Contributing exposure scenario 28

### **Washing and cleaning products (including solvent based products)**

**Cleaners, trigger sprays (all purpose cleaners, sanitary products, glass cleaners) (Consumer)**

#### **List of use descriptors**

Product (Sub-)Categories: PC35: Washing and cleaning products

#### **Operational conditions**

Concentration of the substance in a mixture:

<= 15 % (unless otherwise stated)

Duration and frequency of use:

Covers use up to 128 d/y

1 application per day.

For each use event, covers use amounts up to 0.17 h.

Other relevant operational conditions:

Covers use under typical household ventilation room size of 20 m<sup>3</sup>.

#### **Exposure prediction**

Exposure estimation and reference to its source:

Covers skin contact area up to 428 cm<sup>2</sup>.

For each use event, covers use amounts up to 35 g.

#### **Risk management measures**

Operational conditions and risk management measures:

No specific risk management measure identified beyond those operational conditions stated.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

**INEOS Phenol**

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 116 of 121

Contributing exposure scenario 29

### **Welding and soldering products, flux products (Consumer)**

#### **List of use descriptors**

Product (Sub-)Categories: PC38: Welding and soldering products, flux products

#### **Operational conditions**

Concentration of the substance in a mixture:

<= 20 % (unless otherwise stated)

Duration and frequency of use:

Covers use up to 365 d/y

1 application per day.

For each use event, covers use amounts up to 1 h.

Other relevant operational conditions:

Covers use under typical household ventilation room size of 20 m<sup>3</sup>.

#### **Exposure prediction**

Exposure estimation and reference to its source:

For each use event, covers use amounts up to 12 g.

#### **Risk management measures**

Operational conditions and risk management measures:

No specific risk management measure identified beyond those operational conditions stated.

---

### **Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES**

Shown are the result of the quantitative exposure and risk assessment prepared based on the 'ESIG GES Consumer Tool'. This tool can be downloaded from the ESIG website: <http://www.esig.org/en/regulatory-information/reach/ges-library/consumer-gess>

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 117 of 121

### Exposure Scenario 24: Uses in coatings

#### List of use descriptors

Sector of uses [SU]: SU21: Consumer uses  
Product Categories: PC1: Adhesives, sealants  
PC4: Anti-freeze and de-icing products  
PC5: Artists supply and hobby preparations  
PC9: Coatings and paints, fillers, putties, thinners  
PC10: Building and construction preparations not covered elsewhere  
PC15: Non-metal surface treatment products  
PC24: Lubricants, greases, release products  
PC31: Polishes and wax blends

#### Application

Activities and processes: Covers the use in coatings (paints, inks, adhesives, etc) and including exposures during use (including materials receipt, storage, preparation and transfer from bulk and semi-bulk, application by spray, roller, brush, spreader by hand or similar methods, and film formation) and equipment cleaning and maintenance and associated laboratory activities.

Remark: Product categories [PC] PC1, PC4, PC5, PC9, PC10, PC15, PC24, PC31

Consumer exposure and risk assessment:  
Shown are the result of the quantitative exposure and risk assessment prepared based on the 'ESIG GES Consumer Tool'. This tool can be downloaded from the ESIG website: <http://www.esig.org/en/regulatory-information/reach/ges-library/consumer-gess>

Contributing Scenarios: 1 General information  
Applies to all contributing exposure scenarios related to exposure scenario 24: Uses in coatings (Consumer)

Page 117

Contributing exposure scenario 1

#### General information

**Applies to all contributing exposure scenarios related to exposure scenario 24: Uses in coatings (Consumer)**

#### List of use descriptors

Product (Sub-)Categories: PC1: Adhesives, sealants  
PC4: Anti-freeze and de-icing products  
PC5: Artists supply and hobby preparations  
PC9: Coatings and paints, fillers, putties, thinners  
PC10: Building and construction preparations not covered elsewhere  
PC15: Non-metal surface treatment products  
PC24: Lubricants, greases, release products  
PC31: Polishes and wax blends

#### Operational conditions

Product characteristics: liquid  
Vapour pressure: 24000 Pa

Concentration of the substance in a mixture:  
Unless stated differently, covers percentage substance in the product up to 100 %

Duration and frequency of use:  
Unless stated differently, covers frequency up to 4/d. For each use event, covers use amounts up to 8h.

Other relevant operational conditions:  
Assumes activities are at ambient temperature (unless stated differently). Assumes a room volume of maximum [m<sup>3</sup>]: 20 m<sup>3</sup>. Assumes use with typical ventilation

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

**INEOS Phenol**

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 118 of 121

### Exposure prediction

Exposure estimation and reference to its source:

Unless stated differently, covers use up to 37500 g.  
Covers skin contact area up to 6600 cm<sup>2</sup>.  
refer to GES No. 23 consumer uses

### Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

Shown are the result of the quantitative exposure and risk assessment prepared based on the 'ESIG GES Consumer Tool'. This tool can be downloaded from the ESIG website:  
<http://www.esig.org/en/regulatory-information/reach/ges-library/consumer-gess>

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 119 of 121

### Exposure Scenario 25: Use in cleaning agents

#### List of use descriptors

Sector of uses [SU]: SU21: Consumer uses  
Product Categories: PC3: Air care products  
PC4: Anti-freeze and de-icing products  
PC9: Coatings and paints, fillers, putties, thinners  
PC24: Lubricants, greases, release products  
PC32: Polymer preparations and compounds  
PC35: Washing and cleaning products  
PC38: Welding and soldering products, flux products

#### Application

Activities and processes: Covers general exposures to consumers arising from the use of household products sold as washing and cleaning products, aerosols, coatings, de-icers, lubricants and air care products.

Remark: Product categories [PC] PC3, PC4, PC9, PC24, PC32, PC35, PC38

Consumer exposure and risk assessment:

Shown are the result of the quantitative exposure and risk assessment prepared based on the 'ESIG GES Consumer Tool'. This tool can be downloaded from the ESIG website: <http://www.esig.org/en/regulatory-information/reach/ges-library/consumer-gess>

Contributing Scenarios: 1 General information  
Applies to all contributing exposure scenarios related to exposure scenario 25: Use in cleaning agents (Consumer)

Page 119

Contributing exposure scenario 1

#### General information

**Applies to all contributing exposure scenarios related to exposure scenario 25: Use in cleaning agents (Consumer)**

#### List of use descriptors

Product (Sub-)Categories: PC3: Air care products  
PC4: Anti-freeze and de-icing products  
PC9: Coatings and paints, fillers, putties, thinners  
PC24: Lubricants, greases, release products  
PC32: Polymer preparations and compounds  
PC35: Washing and cleaning products  
PC38: Welding and soldering products, flux products

#### Operational conditions

Product characteristics: liquid  
Vapour pressure: 24000 Pa

Concentration of the substance in a mixture: Unless stated differently, covers percentage substance in the product up to 100 %

Duration and frequency of use: Unless stated differently, covers frequency up to 4/d. For each use event, covers use amounts up to 8h.

Other relevant operational conditions: Assumes activities are at ambient temperature (unless stated differently). Assumes a room volume of maximum [m3]: 20 m<sup>3</sup>. Assumes use with typical ventilation

#### Exposure prediction

Exposure estimation and reference to its source:  
Unless stated differently, covers use up to 37500 g.  
Covers skin contact area up to 6600 cm<sup>2</sup>.  
refer to GES No. 23 consumer uses

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

**INEOS Phenol**

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 120 of 121

### **Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES**

Shown are the result of the quantitative exposure and risk assessment prepared based on the 'ESIG GES Consumer Tool'. This tool can be downloaded from the ESIG website: <http://www.esig.org/en/regulatory-information/reach/ges-library/consumer-gess>



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# INEOS Phenol

## Acetone

Revision date: 7/3/2018  
Version: 14

Language: en-GB,IE

Date of print: 12/3/2018  
Page: 121 of 121

### Exposure Scenario 26: De-icing and anti-icing applications

#### List of use descriptors

Sector of uses [SU]: SU21: Consumer uses  
Product Categories: PC4: Anti-freeze and de-icing products

#### Application

Activities and processes: De-icing of vehicles and similar equipment by spraying.  
Remark: Product categories [PC] 4

Consumer exposure and risk assessment:  
Shown are the result of the quantitative exposure and risk assessment prepared based on the 'ESIG GES Consumer Tool'. This tool can be downloaded from the ESIG website: <http://www.esig.org/en/regulatory-information/reach/ges-library/consumer-gess>

Contributing Scenarios: 1 General information  
Applies to all contributing exposure scenarios related to exposure scenario 26: De-icing and anti-icing applications (Consumer)

Page 121

Contributing exposure scenario 1

#### General information

**Applies to all contributing exposure scenarios related to exposure scenario 26: De-icing and anti-icing applications (Consumer)**

#### List of use descriptors

Product (Sub-)Categories: PC4: Anti-freeze and de-icing products

#### Operational conditions

Product characteristics: liquid  
Vapour pressure: 24000 Pa  
Concentration of the substance in a mixture:  
Unless stated differently, covers percentage substance in the product up to 100 %  
Duration and frequency of use:  
Unless stated differently, covers frequency up to 4/d. For each use event, covers use amounts up to 8h.  
Other relevant operational conditions:  
Assumes activities are at ambient temperature (unless stated differently). Assumes a room volume of maximum [m3]: 20 m<sup>3</sup>. Assumes use with typical ventilation

#### Exposure prediction

Exposure estimation and reference to its source:  
Unless stated differently, covers use up to 37500 g.  
Covers skin contact area up to 6600 cm<sup>2</sup>.  
refer to GES No. 23 consumer uses

### Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

Shown are the result of the quantitative exposure and risk assessment prepared based on the 'ESIG GES Consumer Tool'. This tool can be downloaded from the ESIG website: <http://www.esig.org/en/regulatory-information/reach/ges-library/consumer-gess>